

County Surveyor's Record, Douglas County, Oregon

15338 Dependent Resurvey, Portion of Subdivisional Lines,
T. 32 S., R. 4 W., Willamette Meridian, Oregon

CHAINS							
	<p style="text-align: center;">A shattered chinquapin stump, 8 ins. diam., bears S. 86 1/4° E., 52 1/2 lks. dist., with scribe marks 1/16 18 CS BT visible on open and decayed blaze.</p> <p>Descend 60 ft. over SW. slope.</p>						
37.55	Starvout Creek, 25 lks. wide, course N. 30° W.; asc. 15 ft. over gradual NE. slope.						
38.75	Asphaltic surfaced road, 30 lks. wide, bears N. 70° W., and S. 70° E.						
41.57	The cor. of secs. 7, 12, 13, and 18, on W. bdy. of Tp.						
	<p>Land, mountainous east 3/4 mile, valley bottom west 1/4 mile. Soil, rocky clay east 3/4 mile, clay west 1/4 mile. Timber, fir, pine, cedar, oak, madrone, chinquapin, ash, maple, and alder; undergrowth, reproduction, poison oak, salal, manzanita, arrowwood, Oregon grape, and black- berry.</p>						
	<p>From the cor. of secs. 7 and 18 only, on W. bdy. of sec. 17.</p> <p>N. 1° 06' W., on the E. bdy. of sec. 7.</p> <p>Ascend 135 ft. over SW. slope, through moderate timber and dense undergrowth.</p>						
6.50	Spur, slopes W.; desc. 125 ft. over N. slope.						
10.105	True point for the closing cor. of secs. 8 and 17, on E. bdy. of sec. 7, hereinafter described.						
	Descend 415 ft. over N. slope.						
20.02	Point for the S 1/16 sec. cor. of sec. 7 only.						
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin-left: 100px;"> <table style="border-collapse: collapse;"> <tr><td style="border-right: 1px solid black; padding-right: 5px;">S 1/16</td><td style="padding-left: 5px;"> </td></tr> <tr><td style="border-right: 1px solid black; padding-right: 5px;">S 7</td><td style="padding-left: 5px;"> </td></tr> <tr><td style="border-right: 1px solid black; padding-right: 5px;"></td><td style="padding-left: 5px;">1971</td></tr> </table> </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 8 ins. diam., bears S. 19° W., 101 1/2 lks. dist., mkd. S 1/16 S7 BT.</p> <p style="margin-left: 40px;">A fir, 57 ins. diam., bears N. 23° W., 25 lks. dist., mkd. S 1/16 S7 BT.</p> <p>Descend 35 ft. over NE. slope.</p>	S 1/16		S 7			1971
S 1/16							
S 7							
	1971						
20.90	Creek, 1 lk. wide, course N. 30° W.; asc. 5 ft. over SW. slope.						
21.70	Top of ascent, slopes NW.; desc. 65 ft. over NW. slope.						
24.90	Creek, 1 lks. wide, course W.; asc. 135 ft. over SW. slope.						
29.825	Point for the S 1/16 sec. cor. of sec. 8 only.						
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>						