

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,
T. 32 S., R. 4 W., Willamette Meridian, Oregon.

15339

CHAINS

| S 1/16
| S 8
1971

from which

A fir, 14 ins. diam., bears N. 12 1/4° E., 76 1/2 lks.
dist., mkd. S 1/16 S8 BT.

A fir, 28 ins. diam., bears S. 69° E., 53 lks.
dist., mkd. S 1/16 S8 BT.

Ascend 30 ft. over SW. slope.

32.00 Spur, slopes W.; desc. 55 ft. over NW. slope.

34.00 Ravine, drains N. 80° W.; asc. 45 ft. along W. slope.

38.45 Top of ascent, slopes W.; desc. 15 ft. over NW. slope.

40.04 The 1/4 sec. cor. of secs. 7 and 8, determined at record bearing and distance from the remaining original 1871 bearing tree redescribed in 1897:

A fir, 33 ins. diam., bears S. 50° E., 116 lks.
dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 32 S R 4 W *FND. OK 11/90 M 111-12*
1/4
S 7 | S 8
1971

from which a new bearing tree

A fir, 21 ins. diam. bears N. 61 3/4° W., 54 lks.
dist., mkd. 1/4 S7 BT.

The corner falls in a ravine, drains S. 50° W.

N. 1° 28' W., beginning new measurement.

Ascend 105 ft. over SW. slope.

3.95 Dirt road, 15 lks. wide, bears N. 60° E., and S. 60° W.

4.35 Spur, slopes S. 75° W.; desc. 290 ft. over NW. slope.

12.80 Creek, 3 lks. wide, course S. 70° W.; also power line, bears N. 35° W., and S. 35° E.; asc. 440 ft. over SW. slope.

22.85 Spur, slopes S. 55° W.; desc. 95 ft. over NW. slope.

26.00 Ravine, drains N. 60° W.; asc. 45 ft. along W. slope.

37.85 Spur, slopes NW.; desc. 45 ft. over N. slope.

39.35 The cor. of secs. 5, 6, 7 and 8, perpetuated and recorded by George J. Wendroth, Deputy County Surveyor, in 1963, monumented with an iron pipe, 1 in. diam.,