

# County Surveyor's Record, Douglas County, Oregon

**15340**

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 32 S., R. 4 W., Willamette Meridian, Oregon

**CHAINS**

protruding 14 ins. above the ground, firmly set, at record bearing and distance from the remaining original 1871 bearing trees:

A fir, 21 ins. diam., bears N. 40° E., 9 lks. dist., with healed blaze.

A fir, 25 ins. diam., bears S. 30° W., 11 lks. dist., with scribe mark R visible on partially opened blaze.

and bearing trees mkd. by Bruce A. Shaner, Registered Engineer No. 4906, in 1963

A fir, 21 ins. diam., bears S. 63° E., 50 lks. dist., with pitched over blaze.

A fir, 19 ins. diam., bears N. 25 1/2° W., 30 1/2 lks. dist., with pitched over blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground directly over the iron pipe, with brass cap mkd.

*FND. OK 11/90*      T 32 S R 4 W  
*M III - 12*              S 6 | S 5  
                               S 7 | S 8  
                                   1971

Land, mountainous.  
Soil, rocky clay.  
Timber, fir, pine, yew, oak, madrone, chinquapin, cedar, and maple;; undergrowth, reproduction, salal, Oregon grape, poison oak, vine maple, arrowwood, and manzanita.

S. 88° 49' W., bet. secs. 6 and 7.

Descend 5 ft. along N. slope, through moderate timber and dense undergrowth.

0.70      Spur, slopes NW.; desc. 635 ft. over W. slope.

9.80      Power line, bears NW. and SE.

18.90      Asphaltic surfaced road, 30 lks. wide, bears N. 10° E., and S. 10° W.

19.35      Wire fence bears N. 10° E., and S. 10° W.; enter open field.

19.975      Point for the E 1/16 sec. cor. of secs. 6 and 7.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

E 1/16  $\frac{S\ 6}{S\ 7}$   
 1971

from which

A fir, 16 ins. diam., bears N. 24 3/4° E., 105 1/2 lks. dist., mkd. E 1/16 S6 BT.