

County Surveyor's Record, Douglas County, Oregon

15342

Dependent Resurvey, Portion of Subdivisional Lines,
T. 32 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

20.07

Point for the W 1/16 sec. cor. of secs. 6 and 7.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

W 1/16 $\frac{S\ 6}{S\ 7}$
1971

from which

A white fir, 8 ins. diam., bears N. 3° W., 14 lks. dist., mkd. W 1/16 S6 BT.

A fir, 12 ins. diam., bears S. 8° E., 24 lks. dist., mkd. W 1/16 S7 BT.

Ascend 345 ft. over NE. slope, along S. edge of logged area.

36.00

Spur, slopes S. 70° E.; asc. 50 ft. over SE. slope.

39.74

The cor. of secs. 1, 6, 7, and 12, on W. bdy. of Tp.

Land, mountainous ex-cept for valley bottom
Soil, rocky clay in mountainous portion, clay in bottom.
Timber, fir, pine, cedar, oak, madrone, maple, and alder;
undergrowth, reproduction, poison oak, vine maple, salal,
Oregon grape, arrowwood, blackberry, fern, and wild rose.

From the cor. of secs. 16, 17, 20, and 21, perpetuated and recorded by George J. Wendroth, Deputy County Surveyor, in 1947, monumented with an iron pipe, 1 1/4 ins. diam., protruding 15 ins. above the ground, firmly set, at record bearing and slope distance from the remaining original 1897 bearing trees:

A madrone, 21 ins. diam., bears N. 27° E., 37 1/2 lks. dist., with healed blaze. (Record, and to face, 41 lks.)

A madrone, 13 ins. diam., bears N. 81° W., 21 lks. dist., with opened and decayed blaze.

and bearing trees mkd. by Wendroth

A fir, 10 ins. diam., bears N. 81 1/2° E., 78 lks. dist., with healed double blaze.

A fir, 18 ins. diam., bears S. 80 3/4° E., 59 1/2 lks. dist., with healed double blaze.

A fir, 24 ins. diam., bears S. 11 1/4° W., 67 lks. dist., with healed double blaze.

A black oak, 34 ins. diam., bears N. 61 1/2° W., 140 lks. dist., with healed double blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 32 S R 4 W
S 17 | S 16
S 20 | S 21
1971