

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, **15343**
 T.32 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
	<p>Deposit iron pipe alongside iron post.</p> <p>S. 89° 28' W., bet. secs. 17 and 20.</p> <p>Descend 505 ft. over SW. slope, through heavy timber and dense undergrowth, along N. edge of logged area.</p>
20.04	<p>The E 1/16 sec. cor. of secs. 17 and 20, established and recorded by George J. Wendroth, Deputy County Surveyor, in 1947, monumented with an iron pipe, 1 in. diam., protruding 6 ins. above the ground firmly set, from which bearing trees mkd. by Wendroth:</p> <p>A madrone, 17 ins. diam., bears N. 66° E., 6 lks. dist., with scribe marks 1/16S CS BT visible on partially healed double blaze.</p> <p>A chinquapin, 13 ins. diam., bears S. 40 1/2° E., 33 lks. dist. with scribe marks CS BT visible on partially healed double blaze.</p>
	<p>S. 89° 34' W., beginning new measurement.</p> <p>Descend 175 ft. over W. slope.</p>
9.85	<p>Creek, 1 lk. wide, course SW.; asc. 5 ft. over SE. slope.</p>
9.92	<p>The W-E 1/64 sec. cor. of secs. 17 and 20, established and recorded by George J. Wendroth, Deputy County Surveyor, in 1947, monumented with an iron pipe 3/4 in. diam., protruding 6 ins. above ground, firmly set, from which bearing trees mkd. by Wendroth:</p> <p>A madrone, 11 ins. diam., bears S. 74° E., 65 1/2 lks. dist., with healed double blaze.</p> <p>A madrone, 8 ins. diam., bears S. 4 1/2° W., 45 lks. dist., with scribe marks CS BT visible on partially healed double blaze.</p>
	<p>S. 89° 27' W., beginning new measurement.</p> <p>Ascend 25 ft. over SE. slope changing to S. slope.</p>
4.40	<p>Top of ascent, slopes S.; desc. 100 ft. over SW. slope.</p>
10.08	<p>The 1/4 sec. cor. of secs. 17 and 20, perpetuated and recorded by George J. Wendroth, Deputy County Surveyor, in 1946, monumented with an iron pipe, 3/4 in. diam., protruding 8 ins. above the ground, firmly set, at record bearing and distance from the remaining original 1897 bearing tree:</p> <p>A madrone, 28 ins. diam., bears N. 78° W., 21 lks. dist., with healed blaze. (Rescribed by Wendroth in 1946)</p> <p>and a bearing tree mkd. by Wendroth</p> <p>A fir, 16 ins. diam., bears S. 46° W., 72 1/2 lks. dist., mkd. with healed double blaze.</p> <p>At the corner point</p>