

County Surveyor's Record, Douglas County, Oregon

15344

Dependent Resurvey, Portion of Subdivisional Lines,
T. 32 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground directly over the iron pipe, with brass cap mkd.

T 32 S R 4 W
1/4 S 17
S 20
1971

from which a new bearing tree

A fir, 8 ins. diam., bears N. 28 3/4° E., 72 lks. dist., mkd. 1/4 S17 BT.

S. 89° 40' W., beginning new measurement.

Descend 45 ft. over W. slope, across partially logged area.

4.40 Power and telephone line, bears N. 15° W., and S. 15° E.

4.75 Asphaltic surfaced road, 30 lks. wide, bears N. 15° W., and S. 15° E.

9.99 From this point, a point established and recorded by George J. Wendroth, Deputy County Surveyor, in 1946, bears North, 0.005 chs. dist., monumented with an iron pipe, 1 in. diam., protruding 12 ins. above the ground, firmly set, from which bearing trees mkd. by Wendroth:

A cedar, 15 ins. diam., bears N. 14° W., 47 lks. dist., with scribe mark S visible on partially opened blaze.

A cedar, 15 ins. diam., bears S. 77° E.; 107 1/2 lks. dist., with healed blaze.

Descend 5 ft. over W. slope.

11.65 Starvout Creek, 20 lks. wide, course N. 20° W.; asc. 20 ft. over NE. slope.

12.95 Driveway, 15 lks. wide, bears N. 20° W., and S. 20° E.

~~16.30 Driveway, 15 lks. wide, bears N. 20° W., and S. 20° E.~~

16.30 Creek, 2 lks. wide, course N. 20° E.; asc. 35 ft. over E. slope, changing to NE. slope.

20.015 Point for the W 1/16 sec. cor. of secs. 17 and 20.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

W 1/16 S 17
S 20
1971

from which bearing trees mkd. by Wendroth in 1946

A cedar, 24 ins. diam., bears N. 7° E., 29 lks. dist., with scribe marks 1 S BT visible on partially healed double blaze.

A cedar, 18 ins. diam., bears S. 89 1/2° E., 41 1/2 lks. dist., with healed double blaze.

and a bearing tree of which I have no record