

County Surveyor's Record, Douglas County, Oregon

15345

Dependent Resurvey, Portion of Subdivisional Lines,
T. 32 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

A cedar, 33 ins. diam., bears S. 20 3/4° E., 67 lks. dist., with scribe marks 1/16 S20 CS BT visible on partially healed blaze.

From this point, a point established and recorded by George J. Wendroth, Deputy County Surveyor, in 1946, bears N. 73° 49' E., 0.03 chs. dist., monumented with an iron pipe, 1 in. diam., protruding 10 ins. above the ground, firmly set.

From the same point, another iron pipe of which I have no record, 1 in. diam., protruding 6 ins. above the ground, firmly set, bears S. 64° 50' W., 0.02 chs. dist.

Ascend 25 ft. over NE. slope.

26.255 Intersect E. bdy. of sec. 18.

True point for the closing cor. of secs. 17 and 20.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 32 S R 4 W
S 18 | $\frac{S 17}{S 20}$ CC
1971

from which bearing trees mkd. by the Douglas County Surveyor, in 1970

A cedar, 11 ins. dia., bears N. 47 1/4° E., 8 1/2 lks. dist., with scribe marks T32S R4W S17 CC CS BT visible on open double blaze.

A fir, 9 ins. diam., bears S. 28 1/2° E., 17 1/2 lks. dist., with scribe marks T32S R4W S20 CC CS BT visible on partially healed double blaze.

From this point, the original closing cor. of secs. 17 and 20, bears S. 89° 40' W., 0.105 chs. dist., perpetuated and recorded by the Douglas County Surveyor, in 1970, monumented with an iron pipe, 1 1/4 ins. diam., protruding 15 ins. above the ground, firmly set, with brass cap mkd.

COUNTY SURVEYORS OFFICE
T 32 S R 4 W
S 18 | $\frac{S 17}{S 20}$
CC
1970

from which the remains of the original bearing trees

A sawed and decayed fir stump, 36 ins. diam., bears N. 38° E., 46 lks. dist., no marks visible on burned blaze.

A sawed and decayed fir stump, 26 ins. diam., bears S. 28 1/2° E., 85 lks. dist., with scribe mark B visible on opened blaze. (Record, S. 27° E.)

and bearing trees mkd. by the County Surveyor, in 1970

A cedar, 11 ins. diam., bears N. 71° E., 18 lks. dist., with scribe marks T32S R4W S17 CC CS BT visible on open blaze.