

County Surveyor's Record, Douglas County, Oregon

15346

Dependent Resurvey, Portion of Subdivisional Lines,
T. 32 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

A fir, 9 ins. diam., bears S. 51° E., 24 1/2 lks. dist., with scribe marks T32S R4W S20 CC CS BT visible on partially healed double blaze.

A fir, 6 ins. diam., bears S. 44° W., 21 lks. dist., with scribe marks T32S R4W S18 CC CS BT visible on partially healed double blaze.

Add marks AM 1971 to brass cap.

From the same point, a point established and recorded by George J. Wendroth, Deputy County Surveyor, in 1946, bears S. 35° 55' W., 0.195 chs. dist., monumented with an iron pipe, 1 in. diam., protruding 10 ins. above the ground, firmly set, from which bearing trees mkd. by Wendroth:

A chinquapin snag, 8 ins. diam., bears N. 77 1/2° E., 83 1/2 lks. dist., no marks visible on decayed blaze.

A chinquapin stump, 5 ins. diam., bears S. 11° E., 20 1/2 lks. dist., with illegible scribe marks visible on decayed blaze.

A chinquapin snag, 7 ins. diam., bears S. 59° W., 36 1/2 lks. dist. with scribe marks CS BT visible on partially healed blaze.

From the same point, the SE. cor. of sec. 18 only, bears S. 0° 35' E., 10.24 chs. dist., hereinbefore described.

Land, mountainous except for narrow valley bottom.
Soil, rocky clay.

Timber, fir, cedar, pine, oak, madrone, chinquapin, alder, and maple; undergrowth, reproduction, vine maple salal, poison oak, arrowwood, Oregon grape, manzanita, wild rose, huckleberry, blackberry, and willow.

From the cor. of secs. 16, 17, 20, and 21.

N. 0° 30' E., bet. secs. 16 and 17.

Ascend 55 ft. over SW. slope, through heavy timber and dense undergrowth along W. edge of logged area.

5.70 Top of ascent, slopes W.; desc. 45 ft. over NW. slope.

10.50 Spur, slopes NW.; desc. 470 ft. over NW. slope.

26.25 Creek, 1 lk. wide, course N. 40° W.; asc. 5 ft. along W. slope.

37.50 Top of ascent, slopes W.; desc. 45 fto over NW. slope.

29.50 Creek, 3 lks. wide, course W.; also e. edge of dirt road, 20 lks. wide, bears NW. and SW., on curve; asc. 230 ft. over SW. slope.

40.03 The 1/4 sec. cor. of secs. 16 and 17, perpetuated and recorded by George J. Wendroth, Deputy County Surveyor, in 1948, monumented with an iron pipe, 2 ins. diam., protruding 4 ins. above the ground, firmly set, at record distance from the remains of the original 1897 bearing trees: