

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 32 S., R. 4 W., Willamette Meridian, Oregon

15347

**CHAINS**

A root hole, bears S. 73 3/4° E., 29 lks. dist.,  
alongside of which is a fir, 36 ins. diam., with  
scribe mark 4 visible on partially opened blaze.  
(Record, S. 78° E.)

A root hole, bears S. 83° W., 6 lks. dist.

and a bearing tree mkd. by Wendroth

A ponderosa pine, 17 ins. diam., bears S. 64 1/2° W.,  
27 lks. dist., with scribe marks 1/4 S CS BT visible  
on partially healed double blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins.  
in the ground, with brass cap mkd.

T 32 S R 4 W  
1/4  
S 17 | S 16  
1971

from which a new bearing tree

A cedar, 12 ins. diam., bears S. 55 1/4° E., 29 lks.  
dist., mkd. 1/4 S16 BT.

Deposit iron pipe alongside iron post.

N. 0° 39' E., beginning new measurement.

Ascend 215 ft. over SW. slope changing to S. slope.

- 7.50 Spur, slopes S. 80° W.; desc. 85 ft. over NW. slope.
- 12.00 Spring seepage, 1 lk. wide, course W.; asc. 10 ft. over SW. slope.
- 13.40 Spring seepage, drains W.; asc. 450 ft. over SW. slope.
- 22.20 Power line, bears NW. and SE.
- 22.95 Dirt road, 10 lks. wide, bears NW. and SE.
- 27.00 Same road, bears N. 10° E., and S. 10° W.
- 39.86 The cor. of secs. 8, 9, 16, and 17, perpetuated and  
recorded by George J. Wendroth, Deputy County Surveyor  
in 1948, monumented with an iron pipe, 1 in. diam.,  
protruding 6 ins. above the ground, firmly set, at  
record distance from the remaining original 1897 bearing  
trees:

A fir, 33 ins. diam., bears N. 83° E., 131 lks.  
dist., with healed blaze. (Record, N. 87° E.)

A fir, 41 ins. diam., bears S. 68° E., 71 lks.  
dist., with scribe marks S16 visible on partially  
opened blaze.

A fir, 51 ins. diam., bears S. 56° W., 150 lks.  
dist., with healed blaze.

and a bearing tree mkd. by Wendroth