

County Surveyor's Record, Douglas County, Oregon

15348

Dependent Resurvey, Portion of Subdivisional Lines,
T. 32 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

A madrone, 9 ins. diam., bears N. 68° W., 33lks. dist., with scribe marks S8 CS BT visible on partially healed double blaze.

At the corner point:

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground directly over the iron pipe, with brass cap mkd.

FD. OK 11/90 M 111-12

T 32 S R 4 W	
S 8	S 9
S 17	S 16
1971	

Land, mountainous.
Soil, rocky clay.
Timber, fir, pine, cedar, madrone, oak, chinquapin, and maple; undergrowth, reproduction, vi-e maple, poison oak, Oregon grap, arrowwood, willow, wild rose, blackberry, huckleberry, and manzanita.

S. 89° 38' W., bet. secs. 8 and 17.

Descend 55 ft. along S. slope, through heavy timber and dense undergrowth.

- 6.40 Head of ravine, drains S.; asc. 60 ft. along S. slope.
- 11.25 Top of ascent, slopes S.; desc. 70 ft. over SW. slope.
- 14.05 Ravine, drains S.; asc. 5 ft. along S. slope.
- 20.07 Point for the E 1/16 sec. cor. of sec. 8 only.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

<u>E 1/16 S 8</u>
1971

from which

A fir, 37 ins. diam., bears N. 63 1/2° E., 108 lks. dist., mkd. E 1/16 S8 BT.

A fir, 6 ins. diam., bears N. 47° W., 17 1/2 lks. dist., mkd. E 1/16 S8 BT.

Ascend 5 ft. along S. slope.

- 21.75 Spur, slopes S. 30° W.; desc. 205 ft. over S. slope changing to SW. slope.
- 22.45 Power line, bears NW. and SE.
- 23.20 Dirt road, 10 lks. wide, bears N. and S.
- 28.60 Point for the 1/4 sec. cor. of sec. 8 only, at proportionate distance longitudinally on the N. bdy. of sec. 17.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

FNO. OK 11/90 M 111-12

T 32 S R 4 W	
1/4	S 8
1971	