

County Surveyor's Record, Douglas County, Oregon

15349

Dependent Resurvey, Portion of Subdivisional Lines,
T. 32 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
	<p>from which</p> <p style="margin-left: 40px;">A fir, 26 ins. diam., bears N. 14° E., 96 1/2 lks. dist., mkd. 1/4 S8 BT.</p> <p style="margin-left: 40px;">A fir, 35 ins. diam., bears N. 13° W., 71 lks. dist., mkd. 1/4 S8 BT.</p> <p>Descend 225 ft. over SW. slope.</p>
34.80	Ravine, drains S. 30° W.; asc. 75 ft. over SE. slope.
38.50	Top of ascent, slopes S. 10° W.; desc 45 ft. over SW. slope.
40.365	<p>The 1/4 sec. cor. of sec. 17 only, perpetuated and recorded by the Douglas County Surveyor, in 1970, monumented with an iron pipe, 1 in. diam., protruding 14 ins. above the ground, firmly set, with brass cap mkd. COUNTY SURVEYORS OFFICE T32S R4W 1/4 S8/S17 1970, from which the remains of the original 1897 bearing trees:</p> <p style="margin-left: 40px;">A root hole, bears N. 15° W., 11 lks. dist., alongside of which is lying the remains of a decayed madrone, 12 ins. diam., no marks visible on opened and decayed blaze.</p> <p style="margin-left: 40px;">A root hole, bears S. 8° E., 7 lks. dist., alongside of which is lying the remains of a decayed madrone 11 ins. diam., no marks visible on opened and decayed blaze.</p> <p>and bearing trees mkd. by the County Surveyor</p> <p style="margin-left: 40px;">A fir, 39 ins. diam., bears N. 40° E., 40 lks. dist., with scribe marks 1/4 S8 CS BT visible on partially healed blaze. I destroy the scribe marks on this tree.</p> <p style="margin-left: 40px;">A fir, 39 ins. diam., bears S. 59 3/4° E., 47 1/2 lks. dist., with scribe marks 1/4 S17 CS BT visible on partially healed blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 32 S R 4 W</p> <hr style="width: 10%; margin: 0 auto;"/> <p>1/4 S 17</p> <p>1971</p> </div> <p>from which a new bearing tree</p> <p style="margin-left: 40px;">A fir, 35 ins. diam., bears S. 18 1/2° W., 68 1/2 lks. dist., mkd. 1/4 S17 BT.</p> <p style="margin-left: 40px;">Invert and deposit county pipe alongside iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 22' W., beginning new measurement.</p> <p>Descend 10 ft. over SW. slope.</p>
0.90	Creek, 1 lk. wide course S. 10° W.; asc. 230 ft. over SE. slope.