

County Surveyor's Record, Douglas County, Oregon

15350

Dependent Resurvey, Portion of Subdivisional Lines
T. 32 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

16.70

Spur, slopes S. 50° W.; desc. 180 ft. over NW. slope.

24.25

Head of ravine, drains N.; asc. 35 ft. along N. slope.

27.365

The original closing cor. of secs. 8 and 17, perpetuated and recorded by George J. Wendroth, Deputy County Surveyor, in 1946, monumented with an iron pipe, 1 in. diam., protruding 1 in. above ground, firmly set, from which the remains of the original 1897 bearing trees:

A madrone, 25 ins. diam., bears N. 75° E., 27 lks. dist., with scribe marks S8 visible on partially opened blaze.

A madrone snag, 15 ins. diam., bears S. 52° E., 38 lks. dist., with scribe marks R4W S17 visible on partially opened blaze.

and bearing trees mkd. by Wendroth

A fir, 32 ins. diam., bears N. 75 3/4° E., 56 lks. dist., with healed blaze.

A fir, 33 ins. diam., bears S. 35 1/4° E., 45 1/2 lks. dist., with healed blaze.

Continue along N. slope.

27.65

Intersect the E. bdy. of sec. 7.

True point for the closing cor. of secs. 8 and 17.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

FD. OK
5-91 M113-10

T 32 S R 4 W
S 7 | S 8
S 17 CC
1971

from which bearing trees mkd. by Wenderoth

A fir, 32 ins. diam., bears N. 79 1/2° E., 83 1/2 lks. dist., with healed blaze.

A fir, 33 ins. diam., bears S. 57° E., 66 lks. dist., with healed blaze.

From this point, the cor. of secs. 7 and 18 only, on the W. bdy. of sec. 17, bears S. 1° 06' E., 10.105 chs. dist., hereinbefore described.

Land, mountainous.

Soil, rocky clay.

Timber, fir, pine, cedar, madrone, oak, alder, maple, and chinquapin; undergrowth, manzanita, poison oak, arrowwood, vine maple, Oregongrape, willow, and huckleberry.

Subdivision of Section 7, T. 32 S., R. 4 W.,
Willamette Meridian, Oregon

From the 1/4 sec. cor. of secs. 7 and 18.