

# County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 7, T. 32 S., R. 4 W.,  
Willamette Meridian, Oregon

15351

**CHAINS**

	N. 1° 04' W., on the N. and S. center line of sec. 7, marking and blazing the true line.
	Ascend 175 ft. over SW. slope, through scattering timber and dense undergrowth, along E. edge of logged area.
8.50	Spur, slopes W.; desc. 180 ft. over NW. slope.
13.60	Ravine, drains N. 80° W.; asc. 60 ft. over SW. slope.
17.45	Spur, slopes W.; desc. 50 ft. over NW. slope.
20.185	Point for the center S 1/16 sec. cor. of sec. 7.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	$\begin{array}{c} C \\ S\ 1/16 \left  S\ 7 \\ C \end{array}$ 1971
	from which
	A fir, 16 ins. diam., bears S. 34° E., 24 lks. dist., mkd. CS 1/16 S7 BT.
	A fir, 14 ins. diam., bears N. 78° W., 27 1/2 lks. dist., mkd. CS 1/16 S7 BT.
	Descend 110 ft. over NW. slope, across logged area.
25.10	Ravine, drains N. 40° W.; asc. 15 ft. over SW. slope.
26.85	Top of ascent, slopes W.; desc. 90 ft. over NW. slope.
33.05	Dirt road, 15 lks. wide, bears N. 70° W. and S. 70° E.
37.00	Dirt road, 15 lks. wide, bears N. 50° W., and S. 50° E.
40.30	Wire fence, bears E. and W.; enter open field.
40.37	Point for the center 1/4 sec. cor. of sec. 7, at intersection with the E. and W. center line of sec. 7.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	$\begin{array}{c} C\ 1/4\ S\ 7 \\ 1971 \end{array}$
	from which
	A fir, 13 ins. diam., bears S. 67° E., 148 1/2 lks. dist., mkd. C 1/4 S7 BT.
	A fir, 12 ins. diam., bears S. 42° W., 155 lks. dist., mkd. C 1/4 S7 BT.
	Descend 5 ft. across open field.
60.15	Wire fence at edge of open field, bears N. 65° E. and S. 65° W.
60.45	Point for the center N 1/16 sec. cor. of sec. 7.