

County Surveyor's Record, Douglas County, Oregon


Subdivision of Section 7, T. 32 S., R. 4 W.,
Willamette Meridain, Oregon

15353

CHAINS

- 40.30 The center 1/4 sec. cor. of sec. 7.
Descend 10 ft. over nearly level ground.
- 40.45 Corner of wire fences at edge of open field, extending N., E., and W., bears South, 6 lks. dist.
- 40.95 Dirt road, 15 lks. wide, bears N. and S.
- 60.71 Point for the center W 1/16 sec. cor. of sec. 7.

Set an iron post, 28ins. long, 2 1/2 ins. diam., 8 ins. below the surface of the ground, with brass cap mkd.



from which

An apple tree, 16 ins. diam., bears S. 11° W.,
169 lks. dist., mkd. CW 1/16 S7 BT.

Descend 10 ft. over nearly level ground.

- 67.85 Corner of wire fences, bears N. 40° E., and E.
- 68.50 Asphaltic surfaced road, 30 lks. wide, bears N. 40° E., and S. 40° W.; continue along N. edge of gravelled driveway.
- 81.12 The 1/4 sec. cor. of secs. 7 and 12, on W. bdy. of Tp.

From the center E. 1/16 sec. cor. of sec. 7.

N. 1° 16' W., on the N. and S. center line of the NE 1/4 of sec. 7.

Descend 175 ft. over NW. slope, through heavy timber and dense undergrowth.

- 6.05 Ravine, drains N. 65° W.; asc. 15 ft. over SW. slope.
- 9.85 Top of ascent, slopes W.; desc. 105 ft. over NW. slope.
- 30.15 Bottom of descent, slopes W.; asc. 5 ft. over SW. slope.
- 32.35 Wire fence, bears N. 40° E., and S. 40° W.
- 32.55 Top of ascent and cut bank of road, slopes W.; desc. 20 ft. over NW. slope.
- 33.75 Asphaltic surfaced road, 30 lks. wide, bears N. 20° E., and S. 20° W.
- 35.35 Wire fence, bears N. 10° E., and S. 10° W.
- 39.74 The E 1/16 sec. cor. of secs. 6 and 7.

From the E 1/16 sec. cor. of secs. 7 and 18.

N. 1° 05' W., on the N. and S. center line of the SE 1/4 of sec. 7.

Ascend 275 ft. over S. slope, through heavy timber and dense undergrowth.