

County Surveyor's Record, Douglas County, Oregon

15354

Subdivision of Section 7, T. 32 S., R. 4 W.,
Willamette Meridian, Oregon

CHAINS	
9.85	Spur, slopes W.; desc. 250 ft. over NW slope.
17.05	Ravine, drains N. 70° W.; asc. 25 ft. over SW. slope.
20.095	Point for the Se 1/16 sec. cor. of sec. 7, at inter- section with the E. and W. center line of the SE 1/4 of sec. 7. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. SE 1/16 S 7 1971 from which A fir, 28 ins. diam., bears S. 12 1/2° W., 62 lks. dist., mkd. SE 1/16 S7 BT. A fir, 39 ins. diam., bears N. 35 1/2° E., 115 1/2 lks. dist., mkd. SE 1/16 S7 BT. Ascend slightly over SW. slope.
20.80	Top of ascent, slopes W.; desc. 260 ft. over NW. slope.
27.85	Creek, 2 lks. wide, course S. 70° W.; asc. 160 ft. over SW. slope.
38.30	Spur, slopes S. 70° W., also dirt road, 15 lks. wide, bears N. 70° E., and S. 70° W.; desc. 25 ft. over NW. slope.
40.19	The center E 1/16 sec. cor. of sec. 7.
	From the S 1/16 sec. cor. of sec. 7 only, on E. bdy. of sec. 7. S. 87° 21' W., on the E. and W. center line of the SE 1/4 of sec. 7. Ascend 70 ft. over NE. slope, through heavy timber and dense undergrowth.
2.85	Top of ascent, slopes N.; desc. 105 ft. over NW. slope.
6.40	Ravine, drains N.; asc. 25 ft. along N. slope.
8.55	Top of ascent, slopes N.; desc. 40 ft. along N. slope.
10.65	Ravine, drains N.; asc. 120 ft. over NE. slope.
15.55	Top of ascent, slopes N.; desc. 100 ft. over NW. slope.
20.10	The SE 1/16 sec. cor. of sec. 7. Descend 220 ft. over W. slope.
26.35	Wet ravine, drains NW.; asc. 145 ft. over NE. slope.
33.00	Spur, slopes N. 30° W.; desc. 95 ft. over NW slope.
35.95	Head of ravine, drains NW.; desc. 40 ft. over NW. slope.
40.205	The center S 1/16 sec. cor. of sec. 7.