

# County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 7, T. 32 S., R. 4 W.,  
Willamette Meridian, Oregon

15355

**CHAINS**

From the center W 1/16 sec. cor. of sec. 7.

N. 0° 34' W., on the N. and S. center line of NW 1/4 of sec. 7.

Descend 10 ft. over nearly level ground, across open field.

7.35 Wire fence, bears N. 35° E., and S. 35° W.

8.10 Asphaltic surfaced road, 30 lks. wide, bears N. 35° E., and S. 35° W.

20.045 Point for the NW 1/16 sec. cor. of sec. 7, at intersection with the E. and W. center line of the NW 1/4 of sec. 7.

Set an iron post, 28 ins. long, 2 1/4 ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

NW 1/16 S 7  
1971

from which a bearing tree mkd. by Stewart in 1922

An ash, 21 ins. diam., bears S. 41° W., 30 lks. dist., with scribe marks 1/16 BT visible on partially healed blaze.

and a bearing tree mkd. by Ramsey in 1967

A cedar, 18 ins. diam., bears S. 27° E., 40 lks. dist., with scribe marks NW 1/16 S7 RS404 BT visible on partially healed blaze.

and a new bearing tree

A fir, 16 ins. diam., bears N. 48 1/2° W., 145 lks. dist., mkd. NW 1/16 S7 BT.

From this point, a point established and recorded by G. G. Stewart, Deputy County Surveyor, in 1922, subsequently remonumented by Marvin C. Ramsey, Registered Land Surveyor No. 404, in 1967, with an iron pipe, 1 in. diam., protruding 4 ins. above the ground, firmly set, bears N. 71° E., 0.295 chs. dist.

Descend slightly over NW.slope.

20.50 Cow Creek, 70 lks. wide, course S. 60° W.; asc. 400 ft. over SE. slope.

23.20 Asphaltic surfaced road, 30 lks. wide, bears N. 40° E., and S. 40° W.; also, power line, bears the same.

25.20 Abandoned irrigation ditch, 3 lks. wide, course S. 55° W.

36.00 Spur, slopes E.; desc. 105 ft. over NE. slope.

40.08 The W 1/16 sec. cor. of secs. 6 and 7.

From the center N 1/16 sec. cor. of sec. 7.

S. 87° 30' W., on the E. and W. center line of NW 1/4 of sec. 7.