

County Surveyor's Record, Douglas County, Oregon

15356

Subdivision of Section 7, T. 32 S., R. 4 W.,
Willamette Meridian, Oregon

CHAINS


- Descend 15 ft. over gradual W. slope, across open bottom land.
- 0.43 Asphaltic surfaced road, 30 lks. wide, bears N. 65° E., and S. 65° W.
- 1.40 Wire fence, bears N. 65° E., and S. 65° W.
- 19.85 Wire fence, bears N. 40° E., and S. 40° W.
- 20.23 The NW 1/16 sec. cor. of sec. 7.

Descend 10 ft. over NW slope.
- 21.00 Cow Creek, 70 lks. wide, course S. 60° W.; asc. 100 ft. over SE. slope.
- 24.20 Poer line, bears N. 60° E., and S. 60° W.
- 25.10 Asphaltic surfaced road, 30 lks. wide, bears N. 60° E.,
- 28.70 Abandoned irrigation ditch, 3 lks. wide, course S. 70° W.
- 35.70 Top of ascent, slopes S.; desc. 5 ft. over SW. slope.
- 40.27 The N 1/16 sec. cor. of secs. 7 and 12, on W. bdy. of Tp.

Subdivision of Section 17, T. 43 S., R. 4 W.,
Willamette Meridian, Oregon

- From the 1/4 sec. cor. of secs. 17 and 20.
- N. 0° 22' E., on the N. and S. center line of sec. 17.
- Ascend 300 ft. over SW. slope, through heavy timber and dense undergrowth.
- 18.40 Spur, slopes W.; desc. 30 ft. over NW. slope.
- 20.01 Point for the center S 1/16 sec. cor. of sec. 17.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



from which

- A fir, 13 ins. diam., bears N. 53 3/4° E., 26 lks. dist., mkd. CS 1/16 S17 BT.
- A fir, 19 ins. diam., bears West, 2 lks. dist., mkd. CS 1/16 S17 BT.
- Descend 255 ft. over NW. slope.
- 29.25 Creek, 3 lks. wide, course S. 70° W.; asc. 205 ft. over SW slope.