

# County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 17, T. 32 S., R. 4 W.,  
Willamette Meridian, Oregon

15357

CHAINS	
30.05	Dirt road, 25 lks. wide, bears N. 70° E., and S. 70° W.
40.02	<p>Point for the center 1/4 sec. cor. of sec. 17, at intersection with the E. and W. center line of sec. 17.</p> <p>Set an iron post, 28 ins. long, 2 1/4 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C 1/4 S 17 1971</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 28 ins. diam., bears N. 62° W., 86 lks. dist., mkd. C 1/4 S17 BT.</p> <p style="padding-left: 40px;">A chinquapin, 8 ins. diam., bears S. 23° E., 43 lks. dist., mkd. C 1/4 S17 BT.</p> <p>Ascend 70 ft. along W. slope.</p>
49.30	Dirt road, 25 lks. wide, bears N. 30° W., and S. 30° E.
61.75	Creek, 1 lk. wide, course S. 15° W., from N.; asc. 175 ft. over S. slope.
72.50	Dirt road, 25 lks. wide, bears E. and W.
73.70	Leave creek, course S., from N. 10° W., asc. 140 ft. over SW. slope.
79.96	The 1/4 sec. cor. of sec. 17 only, on N. bdy of sec. 17.
	<p>From the 1/4 sec. cor. of sec. 16 and 17.</p> <p>S. 89° 30' W., on the E. and W. center line of sec. 17.</p> <p>Descend 65 ft. over SW. slope, through heavy timber and dense undergrowth.</p>
4.50	Ravine, drains S. 20° W.; asc. 20 ft. along S. slope.
8.30	Spur, slopes S.; desc. 250 ft. over SW. slope.
17.70	Creek, 2 lks. wide, course S. 35° W.; asc. 85 ft. along S. slope.
19.50	Dirt road, 15 lks. wide, bears N. 35° E., and S. 35° N.
30.75	Spur, slopes S. 20° W.; desc. 75 ft. over SW. slope.
32.00	Dirt road, 25 lks. wide, bears N. 30° W., and S. 30° E.
34.20	Ravine, drains SW.; asc. 45 ft. along S. slope.
37.70	Spur, slopes S.; desc. 20 ft. over SW. slope.
40.14	<p>The center 1/4 sec. cor. of sec. 17.</p> <p>Descend 145 ft. over SW. slope.</p>
45.10	Creek, 2 lks. wide, course S. 20° W.; asc. 270 ft. along S. slope changing to SE. slope.
60.14	Point for the center W. 1/16 sec. cor. of sec. 17.