


County Surveyor's Record, Douglas County, Oregon

15358

Subdivision of Section 17, T. 32 S., R. 4 W.,
Willamette Meridian, Oregon

CHAINS

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



from which

A fir, 51 ins. diam., bears N. 71 ° E., 60 1/2 lks. dist., mkd. CW 1/16 S17 BT.

A fir, 21 ins. diam., bears S. 66° E., 37 lks. dist., mkd. CW 1/16 S17 BT.

Ascend slightly over SE. slope.

60.50 Spur, slopes S. 30° W.; desc. 135 ft. over SW. slope.

67.06 The 1/4 sec. cor. of sec. 17 only, on W. bdy. of sec. 17.

From the W 1/16 sec. cor. of secs. 17 and 20.

N. 0° 23' E., on the N. and S. center line of the SW 1/4 of sec. 17.

Descend 70 ft. over NE. slope, through scattering timber and dense undergrowth, across logged area.

1.50 Dirt road, 15 lks, wide, bears E. and W.


3.15 Power and telephone line, bears N. 80° W. and S. 80° E.

7.10 Starvout creek, 20 lks. wide, course N. 35° W. ; asc. 5 ft. over nearly level ground.

13.95 Creek, 1 lk. wide, course S. 25° W.; asc. 10 ft. over nearly level ground.

19.98 Point for the SW 1/16 sec. cor. of sec. 17, at intersection with the E. and W. center line of the SW 1/4 of sec. 17.

Set an iron post, 28 ins. long 2 1/2 ins. diam., 8 ins. below the surface of the ground, with brass cap mkd.



from which

A double forked cedar, 38 ins. diam., bears N. 15° W. 147 1/2 lks. diam., mkd. SW 1/16 S17 BT.

A fir, 18 ins. diam., bears S. 31 ° W., 158 lks. dist., mkd. SW 1/16 S17 BT.

From this point, an iron pipe, of which I have no record, 1/2 ins. diam., firmly set, protruding 4 ins. above the ground, bears N. 85° W., 0.27 chs. dist.

Ascend 395 ft. over S. slope.

22.70 Asphaltic surfaced road, 30 lks. wide, bears N. 60° W., and S. 60° E.