

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the West Boundary, **15362**
 T. 28 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

DOUGLAS COUNTY SURVEYORS OFFICE

T 28 S
 R S 24 | S 19 R
 5 S 25 | S 30 4
 W 1961 W

from which the remains of the original bearing trees

A root hole, bears N. 80° E., 60 lks. dist., with a down pine alongside, 16 ins. diam., with fragmentary scribe marks visible on burned blaze.

A root hole, bears S. 58° E., 52 lks. dist., with a down cedar alongside, 20 ins. diam., no marks visible.

and the remains of bearing trees mkd. by Byron

A pine snag, 10 ins. diam., bears N. 54° E., 10 lks. dist., with scribe marks T28S R4W S19 CS BT visible on open double blaze.

A cedar snag 17 ins. diam., bears S. 24° E., 16 lks. dist., with scribe marks T28S visible on open and burned blaze.

A cedar snag, 11 ins. diam., bears S. 18° W., 17 lks. dist., with scribe marks T28S R5W S25 CS BT visible on open double blaze.

A pine, 10 ins. diam., bears N. 45° W., 36 lks. dist., with scribe marks T S visible on open double blaze.

and new bearing trees

A pine, 15 ins. diam., bears S. 47° W., 77 lks. dist., mkd. T28S R5W S25 BT.

A pine, 11 ins. diam., bears N. 54° W., 105 lks. dist., mkd. T28S R5W S24 BT.

N. 0° 08' E., bet. secs. 19 and 24, marking and blazing the true line.

Ascend 235 ft. over broken SE. slope, through light timber and undergrowth.

14.65 Spur, slopes E.; desc. 25 ft. over NE. slope.

19.60 Ravine, drains S. 80° E.; asc. 25 ft. over SE. slope

20.49 Point for the S 1/16 sec. cor. of secs. 19 and 24.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, supported in a mound of stone, 3 ft. base, to top, with brass cap mkd.

S 1/16
 S 24 | S 19
 1974

from which

A fir, 7 ins. diam., bears N. 63° E., 98 lks. dist., mkd. S 1/16 S19 BT.