

County Surveyor's Record, Douglas County, Oregon

15363

Dependent Resurvey of a portion of the West Boundary,

T. 28 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

A fir, 10 ins. diam., bears S. 23° W., 63 1/2 lks. dist., mkd. S 1/16 S24 BT.

Ascent 80 ft. over SE slope.

24.10 Spur ridge, bears N. 75° W. and S. 75° E.; desc. 35 ft. over NE. slope.

28.70 Bottom of descent, slopes S. 85° E.; asc. 65 ft. over SE slope.

29.20 Dirt road, 15 lks. wide, bears N. 60° E. and S. 60° W.

35.10 Spur, slopes E.; desc. 10 ft. over NE. slope.

36.10 Draw, drains SE.; asc. 75 ft. over SW. slope.

40.98 The 1/4 sec. cor. of secs. 19 and 24, on the W. bdy. of the Tp., perpetuated and recorded by John Markham, Jr., in 1957. Professional Engineer No. 2880, monumented with an iron pipe, 2 ins. diam., firmly set, projecting 8 ins. above ground, from which the remains of the original bearing trees:

A sawed white oak stump, 26 ins. diam., bears N. 15° E., 235 lks. dist., no marks visible on opened blaze.

and bearing trees mkd. by Markham

A white oak, 10 ins. diam., bears N. 10° E., 221 lks. dist., with healed double blaze.

A white oak, 9 ins. diam., bears N. 40° E., 78 lks. dist., with healed double blaze.

A white oak, 14 ins. diam., bears N. 42° W., 75 1/2 lks. dist., with healed double blaze.

At the corner point

Set an iron post, 28 ins. long 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T 28 S
1/4
R 5 W | R 4 W
S 24 | S 19
1974

Reset iron pipe alongside iron post.

N. 0° 04' W., beginning new measurement.

Ascend 115 ft. over S. slope.

10.72 Dirt road, 15 lks. wide, bears N. 20° E. and S. 20° W.

11.05 Ridge, bears N. 5° E. and S. 5° W.; desc. 75 ft. over NW. slope.

19.66 Point for the N 1/16 sec. cor. of secs. 19 and 24.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.