

County Surveyor's Record, Douglas County, Oregon

15365

Dependent Resurvey of a Portion of the West Boundary
T. 28 S., R. 4 W., Willamette Meridian, Oregon

CHAINS
22.20

Ridge, bears N. 75° W. and S. 75° E.; desc. 405 ft. over NE. slope.

39.46

Point for the 1/4 sec. cor. of secs. 13 and 18, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 28 S
1/4
R 5 W R 4 W
S 13 | S 18
1974

from which

A fir, 8 ins. diam., bears N. 24° E., 72 1/2 lks. dist., mkd. 1/4 S18 BT.

A fir, 8 ins. diam., bears S. 32 1/2° W., 31 lks. dist., mkd. 1/4 S13 BT.

Descent 180 ft. over NW. slope.

48.20

Ravine, drains N. 50° E.; asc. 75 ft. over SE. slope.

53.85

Top of ascent, slopes E.; desc. 525 ft. over NE. slope.

73.75

Dirt road, 15 lks. wide, bears N. 10° W. and S. 10° E.

77.30

Leave same dirt road, bears N. 10° E. and S. 10° W.

78.30

Point selected for the witness cor. to the cor. of secs. 7, 12, 13, and 18.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.

W C
T 28 S
R 5 W R 4 W
S 12 | S 7
S 13 | S 18
1974

from which

An iron post, 28 ins. long, 2 1/2 ins. diam., set 20 ins. in the ground, for a reference monument, bears N. 38 1/2° E., 90 lks. dist., with brass cap mkd. T28S R4W S7 RM 1974 and an arrow pointing to the corner.

A maple, 6 ins. diam., bears S. 58 1/2° E., 198 lks. dist., mkd. X BT.

A fir, 11 ins. diam., bears N. 72 1/2° W., 218 lks. dist., mkd. X BT.

A cedar, 8 ins. diam., bears N. 5° W., 97 1/2 lks. dist., mkd. X BT.