

# County Surveyor's Record, Douglas County, Oregon

**15367**

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 28 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
	<p>A fir, 20 ins. diam., bears S. 88 1/2° W., 12 1/2 lks. dist., with scribe marks T28S R4W S19 BT visible on open blaze.</p> <p>N. 87° 18' W., bet. secs. 18 and 19.</p> <p>Ascend 455 ft. over SE. slope; through heavy timber and moderate undergrowth.</p>
23.50	<p>Ridge, bears N. 60° E. and S. 60° W.; desc. 50 ft. over NW. slope.</p>
23.70	<p>High voltage transmission line, bears N. 15° W. and S. 15° E.</p>
25.00	<p>Dirt road, 15 lks. wide, bears N. 40° E. and S. 40° W.</p>
28.20	<p>Dirt road, 15 lks. wide, bears N. 30° E. and S. 30° W., also bottom of descent, slopes N. 30° E.; asc. 20 ft. over NE. slope.</p>
30.15	<p>Top of ascent, slopes N.; desc. 135 ft. over NW. slope.</p>
39.77	<p>The 1/4 sec. cor. of secs. 18 and 19, determined at record bearing and distance from the remains of the original bearing trees:</p> <p style="padding-left: 40px;">A sawed fir stump, 43 ins. diam., bears S. 14° W., 60 lks. dist., with scribe mark S visible on opened blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; padding: 10px 0;"> <p>T 28 S R 4 W</p> <p style="margin-left: 40px;">S 18</p> <p style="margin-left: 40px;">1/4 s 19</p> <p style="margin-left: 40px;">1974</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears N. 38° E., 19 lks. dist., mkd 1/4 S18 BT.</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears S. 72 1/2° W., 15 lks. dist., mkd. 1/4 S19 BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 88° 02' W., beginning new measurement.</p> <p>Descend 30 ft. over NW. slope.</p>
1.50	<p>Bottom of descent, slopes N. 20° W.; asc. 55 ft. over broken NE. slope.</p>
11.25	<p>Spur, slopes N.; desc. 40 ft. over NW. slope.</p>
13.00	<p>Creek, 2 lks. wide, course N. 5° W.; asc. 250 ft. over general E. slope.</p>
29.50	<p>Spur, slopes N. 5° W.; desc. 180 ft. over W. slope.</p>
37.75	<p>Creek, 4 lks. wide, course N. 15° W.; asc. 5 ft. over NW. slope.</p>