

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, **15368**
 T. 28 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

38.78

The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp.

Land, mountainous.
 Soil, rocky clay.
 Timber, fir, hemlock, cedar, madrone, and pine; undergrowth, salal, poison oak, hazel, young timber, arrowwood, and fern.

From the 1/4 sec. cor. of secs. 17 and 18, perpetuated and recorded by the County Surveyor, in 1961, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

T 28 S R 4 W
 1/4 S 18 | S 17
 1961

from which the remains of the original bearing trees

A fir, 36 ins. diam., bears N. 80° E., 19 lks. dist., with healed blaze.

and a bearing tree mkd. by the County Surveyor

A fir, 25 ins. diam., bears N. 31° W., 34 lks. dist., with healed double blaze.

N. 1° 19' E., bet. secs. 17 and 18.

Ascend 20 ft. over SW. slope, through heavy timber and light undergrowth.

2.35

Ridge, also top of Brushy Butte, bears N. 55° W. and S. 55° E.; desc. 490 ft. over NE. slope.

19.79

Point for the N 1/16 sec. cor. of secs. 17 and 18.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

N 1/16
 S 18 | S 17
 1974

from which

A hemlock, 6 ins. diam., bears S. 44° E., 11 lks. dist., mkd. N 1/16 S17 BT.

A fir, 18 ins. diam., bears N. 39° W., 50 lks. dist., mkd. N 1/16 S18 BT.

Descend 380 ft. over general W. slope.

39.58

Point for the cor. of secs. 7, 8, 17, and 18, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T 28 S R 4 W
 S 7 | S 8
 S 18 | S 17
 1974