

County Surveyor's Record, Douglas County, Oregon

15375

T. 32 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines, township 32 south, range 6 west, Willamette Meridian, Oregon.

The history of surveys pertaining to this resurvey, is as follows:

The north boundary of the township was surveyed by Wells Lake and George W. Hyde, in 1855.

A portion of the subdivisional lines was surveyed by William H. Byars, in 1881.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated August 12, 1945, under Group Number 883, Oregon.

The directions of the lines were determined by the solar compass method and by deflection angles turned from azimuths obtained by direct solar observations.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions. Lost corners were re-established and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein. Only those lines bounding or crossing public lands were blazed. All lines not forming closures were measured twice to preclude error.

The geographic position of the corner of sections 4, 5, 8, and 9, as scaled from the Canyonville, Oregon, quadrangle map, published by the United States Geological Survey, in 1954, is as follows:

Latitude 42° 48.7' N. Longitude 123° 25.5' W.

The mean magnetic declination is 19° 30' E.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 32 S., R. 6 W., Willamette Meridian, Oregon

(Restoring the survey by William H. Byars,
U. S. Deputy Surveyor, in 1881)

Beginning at the cor. of secs. 4, 5, 8, and 9, perpetuated and recorded by John M. Powell, Deputy County Surveyor, in 1967, and subsequently perpetuated and recored by Gary Langlitz, Deputy County Surveyor, in 1974, monumented with an iron post, 1 in. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd.

T	32	S	R	6	W
	S	5	S	4	
	S	8	S	9	
		1974			
		1967			

from which the remains of the original bearing trees