

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, 15376
 T. 32 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

A ponderosa pine snag, 50 ins. diam., bears
 N. 40° W., 35 lks. dist., with scribe marks
 32 S5 T visible on opened blaze.

and a bearing tree found and recorded by Powell

A fir, 18 ins. diam., bears N. 61° E., 37 lks.
 dist., with scribe marks 2S 6W S4 BT visible
 on opened blaze.

and bearing trees mkd. by Powell

A chinquapin, 7 ins. diam., bears S. 59 1/2° E., 22
 lks. dist., with scribe marks T32S R6W S9 BY
 visible on open double blaze.

A madrone, 5 ins. diam., bears S. 72 1/2° W., 32 lks.
 dist., with scribe marks S8 BT visible on open
 double blaze.

and a bearing tree mkd. by Langlitz

A fir, 21 ins. diam., bears N. 29 1/2° W., 94 1/2 lks.
 dist., with scribe marks T32S R6W S5 CS BT
 visible on open double blaze.

N. 0° 29' W., bet. secs. 4 and 5, marking and blazing
 the true line.

Descend 90 ft. over NE. slope, through heavy timber and
 moderate undergrowth.

- 3.45 Draw, drains S. 70° E.; asc. 155 ft. over SW. slope.
- 9.50 Spur, slopes S. 80° E.; desc. 175 ft. over NE. slope.
- 14.35 Creek, 1 lk. wide, course E.; asc. 380 ft. over SE. slope.
- 26.15 Spur, slopes S. 80° E.; desc. 105 ft. over broken NE.
slope.
- 36.55 Ravine, drains S. 70° E.; asc. 35 ft. over S. slope.
- 37.78 The 1/4 sec. cor. of secs. 4 and 5, perpetuated and recorded
by Gary Langlitz, Deputy County Surveyor, in 1974, monu-
mented with an iron post, 1 in. diam., firmly set, pro-
jecting 4 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE
 T 32 S
 S 5 | S 4
 1/4
 R 6 W
 1974

from which the original bearing trees

A fir, 45 ins. diam., bears N. 30° E., 26 lks.
 dist., with scribe marks BT visible on bark
 blaze.

A fir, 35 ins. diam., bears N. 15° W., 34 lks.
 dist. with scribe marks 1/4 visible on bark
 blaze.

and bearing trees mkd. by Langlitz