

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, **15377**
 T. 32 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

A yew, 13 ins. diam., bears S. 75 1/2° E., 56 1/2 lks. dist., with scribe marks 1/4 S4 CS BT visible on open double blaze.

A fir, 30 ins. diam., bears S. 51 ° W., 51 lks. dist., with scribe marks 1/4 S5 CS BT visible on open double blaze.

N. 0° 12' E., beginning new measurement.

Ascend 620 ft. over S. slope.

18.50 Ridge, dividing Middle Creek and Windy Creek drainages, bears N. 65° E. and S. 65° W.; desc. 700 ft. over N. slope.

41.67 The cor. of secs. 4, 5, 32, and 33, on the N. bdy. of the Tp., perpetuated and recored by Louis W. Amort, Registered Engineer No. 2311, in 1960, and subsequently perpetuated and recored by John M. Powell, Deputy County Surveyor, in 1966, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, in a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 31 S R 6 W

S 32 | S 33

S 5 | S 4

T 32 S R 6 W

1966

from which the remains of the original bearing trees

A madrone, 10 ins. diam., bears N. 50° E., 32 lks. dist., no marks visible on open blaze. (Record, N. 47° E.)

A fir, 53 ins. diam., bears S. 34° W., 33 lks. dist., no marks visible on opened blaze.

and the remains of bearing trees mkd. by Amort

A fir, 17 ins. diam., bears N. 56° E., 132 lks. dist., with healed double blaze.

A fir, 22 ins. diam., bears S. 63° E., 58 lks. dist., with healed double blaze.

A sawed fir stump, 22 ins. diam., bears N. 4° W., 53 lks. dist., no marks visible.

Land, mountainous.

Soil, rocky.

Timber, fir, pine, cedar, hemlock, maple, madrone, alder, and chinquapin; undergrowth, hazel, poison oak, Oregon grape, live oak, salal, and fern.

From the cor. of secs. 4, 5, 8, and 9.

S. 89° 59' W., bet. secs. 5 and 8.

Ascend 875 ft. over NE. slope, changing to E., through heavy timber and dense undergrowth, along N. edge of old logged area.