

County Surveyor's Record, Douglas County, Oregon

15378

Dependent Resurvey, Portion of Subdivisional Lines,
T. 32 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

- 24.75 Abandoned dirt road, 15 lks. wide, bears N. 10° E. and SW., in curve.
- 34.15 Ridge, dividing Middle Creek and Windy Creek drainages, bears N. 30° E. and S. 30° W.; desc. 110 ft. over W. slope.
- 37.45 Abandoned dirt road, 15 lks. wide, bears N. 10° W. and S. 10° E.
- 39.12 The 1/4 sec. cor. of secs. 5 and 8, reestablished by Arnold Gibson, RLS No. 359, in 1974, monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above ground, with bronze cap mkd.

OREGON STATE BOARD OF FORESTRY

$$\begin{array}{c} S\ 5 \\ 1/4\ \hline S\ 8 \\ 1974 \\ RS\ 359 \end{array}$$

from which bearing trees mkd. by Gibson

A fir, 36 ins. diam., bears N. 1° E., 32 lks. dist., with scribe marks 1/4 S5 BT visible on open blaze.

A fir, 13 ins. diam., bears S. 34° W., 238 lks. dist., with scribe marks 1/4 S8 BT visible on open blaze.

S. 89° 59' W., beginning new measurement.

Descend 285 ft. over W. slope.

- 7.30 Ravine, drains NW.; asc. 85 ft. along N. slope.
- 16.65 Spur, slopes N. 30° W.; desc. 50 ft. over SW. slope.
- 19.56 A point established by Arnold Gibson, RLS No. 359, in 1974, monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above ground, and in a mound of stone, 4 ft. base, 1 ft. high, with bronze cap mkd.

OREGON STATE BOARD OF FORESTRY

$$\begin{array}{c} S\ 5 \\ W\ 1/16\ \hline S\ 8 \\ 1974 \\ RS\ 359 \end{array}$$

from which bearing trees mkd. by Gibson

A fir, 30 ins. diam., bears N. 10° W., 55 lks. dist., with scribe marks W 1/16 S5 BT RS359 visible on open blaze.

A fir, 40 ins. diam., bears N. 83° W., 67 lks. dist., with scribe marks W 1/16 S8 BT visible on open blaze.

Descend 605 ft. over SW. slope.

- 35.41 Creek, 1 lk. wide, course N. 60° W.; desc. 55 ft. over NW. slope.