

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, 15379
T. 32 S., R. 6 W., Willamette Meridian, Oregon

CHAINS
39.12

The cor. of secs. 5, 6, 7, and 8 perpetuated and recorded by John M. Powell, Deputy County Surveyor, in 1965, monumented with an iron post, 1 in. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 32 S R 6 W

S 6 | S 5

S 7 | S 8

1965

from which the remains of the original bearing trees

A fir, 53 ins. diam., bears N. 81° E., 34 lks. dist., with scribe marks 5 CS BT visible on partially healed double blaze. This tree was rescribed by Powell. (Record, N. 85° E., 30 lks.)

A fir, 50 ins. diam., bears S. 73° W., 34 lks. dist., with fragmentary scribe marks visible on partially healed double blaze. (Record, S. 70° W., 32 lks.)

and a bearing tree mkd. by Powell

A fir, 52 ins. diam., bears N. 83° W., 99 1/2 lks. dist., with scribe marks W S6 CS visible on partially healed double blaze.

Land, mountainous.

Soil, rocky clay.

Timber, fir, cedar, hemlock, pine, madrone, maple, alder, and chinquapin; undergrowth, live oak, poison oak, blackberry, blackcap, Oregon grape, salal, hazel, and fern.

N. 1° 47' W., bet. secs. 5 and 6.

Descend 60 ft. over NW. slope, through moderate undergrowth, along W. edge of timber.

2.25 Creek, 1 lks. wide, course N. 55° W.; asc. 130 ft. over SW. slope.

2.65 East edge of gravelled road, 30 lks. wide, in curve, bears N. 10° W. and S. 15° W.

14.75 Spur, slopes NW.; also enter heavy timber, edge bears E. and W.; desc. 435 ft. over N. slope.

37.25 Creek, 2 lks. wide, course N. 10° W.; desc. 15 ft. over N. slope.

40.00 Point for the 1/4 sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.

T 32 S R 6 W

1/4

S 6 | S 5

1975

from which