

County Surveyor's Record, Douglas County, Oregon

15384

Remonumentation of Certain Original Corner Points,
T. 20 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

A dead Hemlock, 10 ins. diam., bears
S. 46° W., 49 lks. dist., with healed
blaze. (Record, S. 43° W.)

Set a 6 ft. steel fence post alongside the
iron post.

The corner of secs. 23, 24, 25, and 26, monumented with
an iron post, 2 ins. diam., firmly set, projecting 4
ins. above the ground, with brass cap mkd.

T 20 S R 9 W
S 23 | S 24
S 26 | S 25
1954

from which bearing trees marked in 1954

A fir, 17 ins. diam., bears N. 48 1/2° E.,
25 lks. dist., with healed blaze.

A fir, 25 ins. diam., bears S. 23° E.,
29 lks. dist., with fragmentary scribe
marks visible on partially healed blaze.

A fir, 14 ins. diam., bears S. 70° W.,
47 lks. dist., with healed blaze.

A fir, 23 ins. diam., bears N. 67° W.,
10 lks. dist., with fragmentary scribe
marks visible on open and burned blaze.
Rescribed T20S R9W S23 BT on new blaze.
(Record, 20 lks.)

Set a 6 ft. steel fence post alongside the
iron post.

The 1/4 sec. cor. of secs. 24 and 25, monumented with an
iron post, 1 in. diam., firmly set, projecting 8 ins.
above the ground, with brass cap mkd.

1/4 S 24
S 25
1954

from which the remaining original bearing tree

A fir, 60 ins. diam., bears N. 55° W.,
63 lks. dist., with healed blaze.

and a bearing tree marked in 1954

An alder, 20 ins. diam., bears S. 34 1/4° W.,
30 lks. dist., with scribe marks 1/4 S25
BT visible on bark.

Set a 6 ft. steel fence post alongside the
iron post.

(Rehabilitating a corner reestablished by
Thomas A. Tillman and Joseph S. Gawron, in 1953)

The cor. of secs. 26, 27, 34, and 35, monumented with an
iron post, 2 ins. diam., firmly set, projecting 2 ins.
above the ground, and in a mound of stone, 3 ft. base,
to top, with brass cap mkd.