

County Surveyor's Record, Douglas County, Oregon

15385

Remonumentation of Certain Original Corner Points,
T. 20 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

*Fd. OK by
LES ROBERTS
2/27/84 M 96-20*

T 20 S R 9 W
S 27 | S 26
S 34 | S 35
1953

from which bearing trees marked in 1953

A fir, 28 ins. diam., bears N. 83 3/4° E.,
43 lks. dist., with healed blaze.

A fir, 20 ins. diam., bears S. 83 3/4° E.,
38 lks. dist., with healed blaze.

A fir, 18 ins. diam., bears S. 11 1/4° W.,
87 lks. dist., with healed blaze.

A fir, 22 ins. diam., bears N. 45 1/4° W.,
76 lks. dist., with healed blaze.

Set a 6 ft. steel bence post alongside the
iron post.

(Rehabilitating a corner established by William Thiel,
in 1891, and remonumented by Thomas A. Tillman
and Joseph S. Gawron, in 1953)

The 1/4 sec. cor. of secs. 26 and 35, monumeted with an
iron post, 1 ins. diam., firmly set, projecting 2 ins.
above the ground, and in a mound of stone, 3 ft. base,
to top, with brass cap mkd.

*Fd. OK by Les Roberts
2/27/84 M 96-20*

1/4 S 26
S 35
1953

from which bearing trees marked in 1953

A fir, 32 ins. diam., bears N. 45 1/2° E.,
9 lks. dist., with healed blaze.

A fir, 20 ins. diam., bears S. 36 3/4° W.,
12 lks. dist., with healed blaze.

Set a 6 ft. steel fence post alongside the
iron post:

(Rehabilitating a corner reestablished by
Thomas A. Tillman and Joseph S. Gawron, in 1953)

The 1/4 sec. cor. of secs. 26 and 27, monumented with an
iron post, 1 in. diam., firmly set, projecting 10 ins.
above the ground, with brass cap mkd.

*Fd. OK
2/27/84 M 96-20*

1/4
S 27 | S 26
1953

from which bearing trees marked in 1953

A fir, 40 ins. diam., bears S. 3 1/2° E.,
37 lks. dist., with healed blaze.

A hemlock, 14 ins. diam., bears N. 67 1/2° W.,
49 lks. dist., with healed blaze. (Record,