

# County Surveyor's Record, Douglas County, Oregon

15386

Remonumentation of Certain Original Corner Points,  
T. 20 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

N. 69° W.)

Set a 6 ft. steel fence post alongside the iron post.

(Rehabilitating a corner established by William Thiel, in 1891, and remonumented by Thomas A. Tillman and Joseph S. Gawron, in 1953)

The cor. of secs. 22, 23, 26, and 27, monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd.

T 20 S. R 9 W.	
S 22	S 23
S 27	S 26
1953	

from which bearing trees marked in 1953

An alder, 25 ins. diam., bears N. 9° E., 37 lks. dist., with scribe marks T20S R9W S23 BT visible on bark.

A cedar, 24 ins. diam., bears S. 47° E., 50 lks. dist., with scribe marks T20S R9W S26 BT visible on bark.

A cedar, 22 ins. diam., bears S. 4° W., 71 lks. dist., with scribe marks T20S R9W S27 BT visible on bark.

An alder, 24 ins., diam., bears N. 52° W., 59 lks. dist., with scribe marks T20S R9W S22 BT visible on bark.

Set a 6 ft. steel fence post alongside the iron post.

(Rehabilitating a corner reestablished by Thomas A. Tillman and Joseph S. Gawron, in 1953)

The 1/4 sec. cor. of secs. 22 and 23, monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd.

1/4	
S 22	S 23
1953	

from which the remaining bearing tree marked in 1953

A double maple, 25 ins. diam., bears S. 45° E., 70 lks. dist., no marks remaining on burned blaze. Rescribed 1/4 S23 BT on new blaze. (Record, S. 46 1/2° E.)

and a new bearing tree

A maple, 10 ins. diam., bears N. 57 1/2° W., 89 lks. dist., mkd. 1/4 S22 BT.

Set a 6 ft. steel fence post alongside the iron post.