

# County Surveyor's Record, Douglas County, Oregon

15388

Remonumentation of Certain Original Corner Points,  
T. 20 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

from which bearing trees marked in 1953

A maple, 37 ins. diam., bears S. 37° E.,  
30 lks. dist., with healed blaze. (Record,  
S. 43 1/2° E.)

A cedar, 50 ins. diam., bears N. 46° W.,  
33 lks. dist., no marks visible on burned  
blaze. Rescribed 1/4 S28 BT on new blaze.

(Rehabilitating corners established by  
William Thiel, in 1891, and remonumented by  
Thomas A. Tillman and Joseph S. Gawron, in 1953)

The cor. of secs. 28, 29, 32, and 33, determined at  
record bearing and distance from bearing trees and  
reference monuments established in 1953

A fir, 40 ins. diam., bears N. 44 1/4° E.,  
122 lks. dist., with fragmentary scribe  
marks visible on partially healed blaze.

An iron post, 2 ins. diam., firmly set,  
projecting 8 ins. above the ground, bears  
N. 45° E., 90 lks. dist., with brass cap mkd.  
T20S R9W S28 RM 1953, and an arrow pointing  
to the corner.

A fir, 38 ins. diam., bears S. 73 1/2° E.,  
106 lks. dist., with fragmentary scribe  
marks visible on partially healed blaze.

An iron post, 2 ins. diam., firmly set,  
projecting 8 ins. above the ground, bears  
S. 45° W., 90 lks. dist., with brass cap  
mkd. T20S R9W S32 RM 1953 and an arrow  
pointing to the corner.

A fir, 28 ins. diam., bears S. 50° W.,  
83 lks. dist., with fragmentary scribe  
marks visible on partially healed blaze.

A fir, 31 ins. diam., bears N. 13 3/4° W.,  
175 lks. dist., with healed blaze.

Set a 6 ft. steel fence post alongside the  
NW. reference monument.

The corner point is located in center line of Smith River  
Road, 30 lks. wide, bears N. 30° W. and S. 30° E.

The 1/4 sec. cor. of secs. 28 and 33, monumented with an  
iron post, 1 in. diam., firmly set projecting 6 ins.  
above the ground, with brass cap mkd.

1/4  $\frac{S\ 28}{S\ 33}$   
1953

from which bearing trees marked in 1953

A maple, 26 ins. diam., bears N. 66° W.,  
25 lks. dist., with fragmentary scribe  
marks visible on partially healed blaze.

A fir, 45 ins. diam., bears S. 13 1/4° E.,