

County Surveyor's Record, Douglas County, Oregon

15392

Dependent Resurvey, Portion of Subdivisional Lines,
T. 26S., R. 3 W., Willamette Meridian, Oregon

CHAINS

Beginning at the cor. of secs. 25, 26, 35, and 36, perpetuated and recorded by Thomas E. Shrum, Registered Engineer, No. 4287, in 1962, subsequently perpetuated by Vernon R. Tracy, Deputy County Surveyor, in 1966, monumented with an iron post, 2 ins. diam, firmly set, protruding 10 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 26 S
S 26 | S 25
S 35 | S 36
R 3 W
1966

from which the remains of the original bearing trees

A fir, 25 ins. diam., bears S. 35° W., 20 lks. dist., with scribe mark S. visible on opened blaze.

A fir, stump, 36 ins. diam., bears N. 30° W., 32 lks. dist., with illegible scribe marks visible on weathered bark blaze.

and bearing trees mkd. by Shrum

A yew, 8 ins. diam., bears N. 57° E., 41 lks. dist., with scribe marks S 25 BT visible on partially healed blaze.

A maple, 11 ins. diam., bears S. 71° E., 70 lks. dist., with scribe marks S36 BT visible on partially healed blaze.

A cedar, 20 ins. diam., bears N. 85° W., 46 lks. dist., with scribe marks S26 BT visible on partially healed blaze.

N. 0° 09' W., bet. secs. 25 and 26, marking and blazing the true line.

Ascend 820 ft. over SW. slope, through scattering timber and light undergrowth.

39.93

Point for the 1/4 sec. cor. of secs. 25 and 26, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T 26 S R 3 W
1/4
S 26 | S 25
1972

from which

A fir, 20 ins. diam., bears N. 51° E., 26 lks. dist., mkd. 1/4 S25 BT.

A fir, 15 lks. diam., bears N. 69° W., 25 lks. dist., mkd. 1/4 S26 BT.

Ascend 150 ft. over SW. slope.

56.85

Gravelled road, 20 lks. wide, bears N. 40° E. and S. 40° W.