

# County Surveyor's Record, Douglas County, Oregon

15394

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 26 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

from which the remains of the original bearing trees

A fir, 40 ins. diam., bears N. 10° E., 23 lks. dist., with fragmentary scribe marks visible on weathered bark blaze. (Record, N. 40° E.)

A root crown, bears S. 10° E., 15 lks. dist., with a down fir alongside, 25 ins. diam., with scribe marks BT visible on opened blaze.

and bearing trees mkd. by Byron

A fir, 14 ins. diam., bears N. 89° E., 5 lks. dist., with healed blaze.

A sugar pine, 12 ins. diam., bears S. 78° E., 48 lks. dist., with healed blaze.

N. 88° 56' W., bet. secs. 24 and 25.

Descend 720 ft. over NW. slope, through heavy timber and light undergrowth.

25.95 Dirt road, 20 lks. wide, bears N. 15° W. and S. 15° E.

40.07 The cor. of secs. 23, 24, 25, and 26.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, chinquapin, maple, alder, and madrone; undergrowth, vine maple, hazel, fern, salal, Oregon grape, and poison oak.

N. 1° 14' E., bet. secs. 23 and 24.

Descend 110 ft. over N. slope, through heavy timber and undergrowth.

5.65 Creek, 3 lks. wide, course S. 75° W.; asc. 325 ft. over S. slope.

20.70 Ridge, bears E. and W.; desc. 25 ft. over N. slope.

39.94 The 1/4 sec. cor. of secs. 23 and 24, perpetuated and recorded by Vernon R. Tracy, Deputy County Surveyor, in 1965, monumented with an iron post, 2 ins. diam., firmly set, protruding 10 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 26 S  
1/4 S 23 | S 24  
R 3 W  
1965

from which the remains of the original bearing trees

A cedar stump, 35 ins. diam., bears S. 85° E., 25 lks. dist., with fragmentary scribe marks visible on decayed opened blaze.

and a bearing tree mkd. by Tracy

A cedar, 18 ins. diam., bears N. 76° E., 68 lks. dist., with scribe marks 1/4 S24 CS BT visible on partially healed double blaze.

and a new bearing tree