

# County Surveyor's Record, Douglas County, Oregon

15396

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 26 S. R. 3 W. Willamette Meridian, Oregon

CHAINS  
40.26

Point for the cor. of secs. 26, 27, 34, and 35, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 26	S R 3 W
S 27	S 26
S 34	S 35
1972	

from which

A cedar, 7 ins. diam., bears N. 66° E., 59 lks. dist., mkd. T26S R3W S26 BT.

A fir, 7 ins. diam., bears S. 61° E., 50 lks. dist., mkd. T26S R3W S35 BT.

A cedar, 13 ins. diam., bears S 51° W., 38 lks. dist., mkd. T26S R3W S34 BT.

A fir, 6 ins. diam., bears N. 76° W., 36 lks. dist., mkd. T26S R3W S27 BT.

From this point, a locally established corner of no record, bears S. 55° 48' W., 0.155 chs. dist., monumented with an iron pipe, 1/2 in. diam., firmly set, protruding 8 ins. above ground.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, maple, and alder; undergrowth, vine maple, hazel, fern, salal, and Oregon grape.

From the cor. of secs. 25, 26, 35, and 36.

S. 89° 53' W., bet. secs. 26 and 35.

Ascend 15 ft. over SE. slope, through heavy timber and dense undergrowth.

2.20 Spur, slopes S. 15 W.; desc. 115 ft. over SW. slope.

3.45 Dirt road, 30 lks. wide, bears N. 35° W. and S. 35° E.

15.10 Creek, 3 lks. wide, course S. 10° W.; asc. 145 ft. over SE slope.

35.85 Spur, slopes S. 30° E.; desc. 30 ft. over SW. slope.

39.75 Gravelled road, 30 lks. wide, bears N. 40° E. and S. 40° W.

40.28 Point for the 1/4 sec. cor. of secs. 26 and 35, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 40 ins. in the ground, with the top 12 ins. below surface of ground, with brass cap mkd.

T 26	S R 3 W
1/4	S 26
	S 35
1972	