

# County Surveyor's Record, Douglas County, Oregon

15401

Dependent Resurvey, Portion of Subdivisional Lines  
T. 26 S., R. 3 W., Willamette Meridian, Oregon

CHAINS	
	<p>A fir snag, 40 ins. diam., bears N. 52° W., 37 lks. dist., with scribe marks T26S R3W S15 BT visible on bark blaze.</p> <p>and bearing trees mkd. by a Boyer, in 1944</p> <p>A chinquapin, 14 ins. diam., bears N. 71° E., 40 lks. dist., with healed blaze.</p> <p>A fir, 15 ins. diam., bears S. 71° E., 35 lks. dist., with healed blaze.</p> <p>and bearing trees mkd. by Byron</p> <p>A fir, 9 ins. diam., bear S. 22 1/2° E., 5 1/2 lks. dist., with healed blaze.</p> <p>A hemlock, 12 ins. diam., bears N. 80° W., 26 lks. dist., with healed blaze.</p> <p>Land, mountainous. Soil, rocky clay loam. Timber, fir, cedar, hemlock, alder, maple, madrone, dogwood, oak, and chinquapin; undergrowth, vine maple, hazel, fern, salal, poison oak, and ocean spray.</p>
	<p>From the cor. of secs. 26, 27, 34, and 35.</p> <p>N. 89° 36' W., bet. secs. 27 and 34.</p> <p>Ascend 275 ft. over SE. slope, through heavy timber and light undergrowth.</p>
13.50	Spur, slopes S. 10° W.; desc. 165 ft. over SW. slope.
15.30	Dirt road, 10 lks. wide, bears N. 50° W. and S. 50° E.
19.895	Point for the E 1/16 sec. cor. of secs. 27 and 34.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	$E \frac{1}{16} \begin{array}{l} S \ 27 \\ S \ 34 \end{array}$ 1972
	from which
	<p>A fir, 10 ins. diam., bears N. 61° E., 32 lks. dist., mkd. E 1/16 S27 BT.</p> <p>A cedar, 38 ins. diam., bears S. 7° W., 24 lks. dist., mkd. E 1/16 S34 BT.</p>
	Descend 305 ft. over SW. slope.
31.10	Creek, 2 lks. wide, course S. 30° W.; asc. 95 ft. over SE slope.
32.40	Dirt road, 10 lks. wide, bears N. 20° E. and S. 20° W.
34.55	Spur, slopes S.; desc. 70 ft. over W. slope.
36.10	Creek, 2 lks. wide, course S.; asc. 160 ft. over E slope.