

County Surveyor's Record, Douglas County, Oregon

15402

Dependent Resurvey, Portion of Subdivisional Lines,
T. 26 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

39.79

Point for the 1/4 sec. cor. of secs. 27 and 34, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T 26 S R 3 W
1/4 $\frac{S\ 27}{S\ 34}$
1972

from which

A madrone, 10 ins. diam., bears N. 12° W., 60 lks. dist., mkd. 1/4 S27 BT.

A fir, 9 ins. diam., bears S. 37° W., 39 lks. dist., mkd. 1/4 S34 BT.

Ascend 20 ft. over E. slope.

42.30

Spur, slopes S. 10° E.; desc. 125 ft. over SW. slope.

79.58

The cor. of secs. 27, 28, 33, and 34, perpetuated and recorded by Floyd Frear, Deputy County Surveyor, in 1949, subsequently perpetuated by Vernon R. Tracy, Deputy County Surveyor, in 1966, monumented with an iron post, 2 ins. diam., with top 12 ins. below surface of ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE
T 26 S
 $\frac{S\ 28\ | S\ 27}{S\ 33\ | S\ 34}$
R 3 W
1966

from which the remains of the original bearing trees

A white oak, 26 ins. diam., bears N. 15° E., 316 lks. dist., with healed blaze.

and the remains of bearing trees mkd. by Frear

A maple stump, 14 ins. diam., bears N. 56° W., 220 lks. dist., with scribe marks BT visible on partially healed blaze.

and bearing trees mkd. by Tracy

A white oak, 10 ins. diam., bears N. 14° E., 284 lks. dist., with healed blaze.

A maple, 13 ins. diam., bears N. 32° W., 310 lks. dist., with healed blaze.

No suitable bearing trees available in south quadrants.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, cedar, hemlock, oak, maple, madrone, alder, and chinquapin; undergrowth, vine maple, hazel, fern, salal, and Oregon grape.