

County Surveyor's Record, Douglas County, Oregon

15403

Dependent Resurvey, Portion of Subdivisional Lines,
T. 26 S., R. 3 W., Willamette Meridian, Oregon

CHAINS	
	N. 0° 26' W., bet. secs. 27 and 28.
	Ascend 10 ft. over SE. slope, over open ground.
4.30	Creek, 8 lks. wide, course S. 50° W.; asc. 95 ft. along E. slope.
4.70	Dirt road, 15 lks. wide, bears NE. and SW.
6.25	Wooden rail fence, extends N. 75° E. and S. 75° W.
12.95	Creek, 3 lks. wide, course S. 30° E.; asc. 355 ft. over SE. slope.
37.45	Dirt road, 15 lks. wide, bears N. 80° W. and S. 80° E.
40.32	Point for the 1/4 sec. cor. of secs. 27 and 28, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.
	T 26 S R 3 W 1/4 S 28 S 27 1975
	from which
	A fir, 28 ins. diam., bears S. 84° E., 11 lks. dist., mkd. 1/4 S27 BT.
	A fir, 9 ins. diam., bears S. 47° W., 30 lks. dist., mkd. 1/4 S28 BT.
	Ascend 200 ft. over SE. slope.
59.15	Barbed wire fence, extended N. 10° W. and S. 10° E.
60.48	Point for the N 1/16 sec. cor. of secs. 27 and 28.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.
	N 1/16 S 28 S 27 1975
	from which
	A cedar, 9 ins. diam., bears N. 57° E., 69 1/2 lks. dist., mkd. N 1/16 S27 BT.
	A cedar, 15 ins. diam., bears S. 80° W., 33 lks. dist., mkd. N 1/16 S28 BT.
	Ascend 275 ft. over SE. slope.
62.65	Barbed wire fence, extends N. 40° E. and S. 40° W.
78.05	Spur, slopes S. 60° E.; desc. 5 ft. over nearly level ground.