

County Surveyor's Record, Douglas County, Oregon

15405

Dependent Resurvey, Portion of Subdivisional Lines
T. 26 S., R. 3 W., Willamette Meridian, Oregon

CHAINS	
	<p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A cedar, 24 ins. diam., bears N. 10° W., 34 lks. dist., with scribe mark S visible on opened blaze.</p> <p>and bearing trees mkd. by Byron</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears N. 30° W., 43 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears S. 63° E., 92 lks. dist., with healed blaze.</p>
	<hr style="width: 20%; margin: 0 auto;"/> <p>N. 88° 29' W., beginning new measurement.</p>
8.65	Creek, 3 lks. wide, course S. 30° E.; asc. 160 ft. over E. slope.
15.10	Spur, slopes S. 10° W.; desc. 140 ft. over SW. slope.
19.92	Point for the W 1/16 sec. cor. of secs. 22 and 27.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.
	<p>W 1/16 $\frac{S\ 22}{S\ 27}$</p> <p>1975</p>
	<p>from which</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears N. 80° E., 25 lks. dist., mkd. W 1/16 S22 BT.</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears S. 51° E., 67 lks. dist., mkd. W 1/16 S27 BT.</p> <p>Descend 15 ft. over SW. slope.</p>
20.20	Creek, 2 lks. wide, course S. 10° W.; asc. 80 ft. over SE. slope.
24.60	Spur, slopes S. 10° W.; desc. 110 ft. over SW. slope.
35.25	Creek, 4 lks. wide, course S. 30° E.; asc. 65 ft. over SE. slope.
39.84	The cor. of secs. 21, 22, 27, and 28.
	<p>Land, mountainous. Soil, rocky clay loam. Timber, fir, cedar, hemlock, maple, madrone, alder, and chinquapin; undergrowth, vine maple, hazel, Oregon grape, salal, and fern.</p>
	<p>Subdivision of Section 26, T. 26 S., R. 3 W., Willamette Meridian, Oregon</p>
	<p>From the 1/4 sec. cor. of secs. 26 and 35.</p> <p>N. 0° 11' W., on the N. and S. center line of sec. 26, marking and blazing the true line.</p>