

# County Surveyor's Record, Douglas County, Oregon

15406

Subdivision of Section 26,  
T. 26 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

Descend 95 ft. over NW. slope, through heavy timber and dense undergrowth.

0.25 Gravelled road, 20 lks. wide, bears N. 30° E. and S. 30° W.

10.50 Ravine, drains S. 40° W.; asc. 20 ft. over SW. slope.

20.02 Point for the center S 1/16 sec. cor. of sec. 26.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

C  
S 1/16 | S 26  
C  
1972

from which

A fir, 55 ins. diam., bears S. 22° E., 41 lks. dist., mkd. CS 1/16 S26 BT.

A fir, 6 ins. diam., bears S. 47° W., 38 lks. dist., mkd. CS 1/16 S26 BT.

Corner is located on spur, slopes W.

Descend 10 ft. over NW. slope.

22.40 Creek, 2 lks. wide, course S. 55° W.; asc. 170 ft. over SW. slope.

35.20 Spur, slopes W.; desc. 80 ft. over N. slope.

40.04 Point for the center 1/4 sec. cor. of sec. 26, at intersection with the E. and W. center line.

Set an iron post, 28 ins. long 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T 26 S R 3 W  
C 1/4 S 26  
1972

from which

A maple, 6 ins. diam., bears N. 19° E., 16 lks. dist., mkd. C 1/4 S26 BT.

A fir, 8 ins. diam., bears S. 8° E., 29 lks. dist., mkd. C 1/4 S26 BT.

Corner is located in ravine, drains W.

Ascend 210 ft. over S. slope.

51.60 Gravelled road, 20 lks. wide, bears S. 40° E. and N. 40° W.

56.75 Spur, slopes W.; desc. 30 ft. over NW. slope.

60.05 Point for the center N 1/16 sec. cor. of sec. 26.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 40 ins. in the ground, with the top 12 ins. below surface of ground, with brass cap mkd.