

County Surveyor's Record, Douglas County, Oregon

15407

Subdivision of Sections 26,
T. 26 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

$$\begin{array}{c} C \\ N\ 1/16\ | \ S\ 26 \\ C \\ 1972 \end{array}$$

from which

A fir, 6 ins. diam., bears S. 2° E., 49 lks.
dist., mkd. CN 1/16 S26 BT.

A fir, 6 ins. diam., bears N. 12° W., 50 lks.
dist., mkd. CN 1/16 S26 BT.

Descend 80 ft. over NW. slope.

- 60.35 Gravelled road, 20 lks. wide, bears N. 40° E. and S. 40° W.
- 66.20 Ravine, drains S. 40° W.; asc. 195 ft. over SE. slope.
- 80.06 The 1/4 sec. cor. of secs. 23 and 26.

From the 1/4 sec. cor. of secs. 25 and 26.

N. 89° 59' W., on the E. and W. center line of sec. 26.

Descend 70 ft. over SW. slope, through heavy timber and light undergrowth.

- 4.35 Creek, 1 lk. wide, course S. 10° W.; asc. 70 ft. over NE. slope.
- 5.95 Gravelled road, 20 lks. wide, bears N. 30° E. and S 30° W.
- 10.25 Spur, slopes S. 10° W.; desc. 270 ft. over W. slope.
- 17.25 Gravelled road, 20 lks. wide, bears S. 50° E. and S. 5° W., in curve.
- 20.14 Point for the center E 1/16 sec. cor. of sec. 26.
Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} C\ E\ 1/16\ C \\ S\ 26 \\ 1972 \end{array}$$

from which

A fir, 6 ins. diam., bears N. 14° E., 37 lks.
dist., mkd. CE 1/16 S 26 BT.

A fir, 6 ins. diam., bears S. 15° E., 33 lks.
dist., mkd. CE 1/16 S26 BT.

Descend 550 ft. over SW. slope.

- 35.05 Gravelled road, 20 lks. wide, bears N. 20° E. and S. 65° W, in curve.
- 40.28 The center 1/4 sec. cor. of sec. 26.
Descend 165 ft. over SW. slope.
- 48.10 Rattlesnake Creek, 10 lks. wide, course S. 10° W.; asc. 300 ft. over SE. slope.