

County Surveyor's Record, Douglas County, Oregon

15409

Subdivision of Section 26,
T. 26 S., R. 3 W., Willamette Meridian, Oregon

CHAINS 33.85	Spur, slopes S. 80° W.; desc. 45 ft. over NW. slope.
39.98	The E 1/16 sec. cor. of secs. 23 and 26.
<p>From the N 1/16 sec. cor. of secs. 25 and 26.</p> <p>N. 89° 56' W., on the E. and W. center line of the NE 1/4 of sec. 26.</p> <p>Descend 400 ft. over W. slope, through heavy timber and light undergrowth.</p>	
20.13	The NE 1/16 sec. cor. of sec. 26.
40.25	The center N 1/16 sec. cor. of sec. 26.
<p>From the W 1/16 sec. cor. of secs. 26 and 35.</p> <p>N. 0° 09' W., on the N. and S. center line of the SW 1/4 of sec. 26.</p> <p>Descend 220 ft. over NW. slope, through scattering timber and light undergrowth.</p>	
15.55	Rattlesnake Creek, 5 lks. wide, course S. 60° W.; asc. 175 ft. over SW. slope.
20.06	<p>Point for the SW 1/16 sec. cor. of sec. 26, at intersection with the E. and W. center line of the SW 1/4 of sec. 26.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SW 1/16 S26 1972</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears S. 88° E., 7 lks. dist., mkd. SW 1/16 S26 BT.</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears S. 54° W., 14 lks. dist., mkd. SW 1/16 S26 BT.</p> <p>Ascend 390 ft. over SW slope.</p>
40.10	The center W 1/16 sec. cor. of sec. 26.
<p>From the center S 1/16 sec. cor. of sec. 26.</p> <p>N. 89° 59' W., on the E. and W. center line of the SW 1/4 of sec. 26.</p> <p>Descend 70 ft. over SW. slope, through heavy timber and dense undergrowth.</p>	
1.60	Creek, 2 lks. wide, course S. 50° W.; asc. 70 ft. over E. slope.
3.75	Spur, slopes N. 40° W.; desc. 280 ft. over SW. slope.
14.60	Rattlesnake Creek, 5 lks. wide, course S. 10° W.; asc. 105 ft. over SE. slope.