

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,
T. 28 S., R. 7 W., Willamette Meridian, Oregon

15413

CHAINS

A fir, 34 ins. diam., bears N. 28 1/2° E., 38 lks. dist., with healed blaze.

A fir, 43 ins. diam., bears N. 37 1/2° W., 34 lks. dist., with healed blaze. This tree was re-scribed in 1935, by Frear, with scribe marks BT visible on bark blaze.

and a reference monument established by Frear, in 1917, and rehabilitated by Byron, in 1971

An iron post, 1 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T28S R7W S14 S15 S22 S23 WC 25 ft. S 1971, bears North, 0.38 chs. dist.

and bearing trees mkd. by Byron

A fir, 12 ins. diam., bears S. 80 1/2° E., 99 lks. dist., with scribe marks WC T28S R7W S23 CS BT visible on open double blaze.

A fir, 22 ins. diam., bears N. 53 1/2° W., 184 1/2 lks. dist., with healed blaze.

N. 84° 23' W., bet. secs. 15 and 22, marking and blazing the true line.

Ascend 60 ft. over NE. slope, through scattering timber and dense undergrowth.

1.90 Power line, bears N. 60° W., and S. 60° E.

10.02 Intersect the W. bdy. of Donation Land Claim No. 47, and point for crossing closing cor.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 28 S		
CCC	S 15 S 22	C 47
		R 7 W
		1975

from which

A fir, 9 ins. diam., bears N. 66° W., 48 lks. dist., mkd. T28S R7W S15 CCC BT.

A fir, 17 ins. diam., bears S. 48 1/4° W., 49 lks. dist., mkd. T28S R7W S22 CCC BT.

From this point, the exterior cor. on the S. bdy. of Claim No. 47, bears S. 0° 04' W., 0.08 chs. dist., hereinafter described.

Corner is located on a spur, slopes N.

Descend 25 ft. over NW slope.

15.40 Ravine, drains N. 10° E.; asc. 40 ft. over NE slope.

19.01 Point for the E 1/16 sec. cor. of secs. 15 and 22.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.