

# County Surveyor's Record, Douglas County, Oregon

15414

Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 28 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

E 1/16  $\frac{S\ 15}{S\ 22}$   
1975

from which

A fir, 9 ins. diam., bears N. 79° W., 45 1/2 lks.  
dist., mkd. E 1/16 S15 BT.

A white fir, 9 ins. diam., bears S. 48 1/4° W., 21  
lks. dist., mkd. E 1/16 S22 BT.

Ascend 385 ft. over SE. slope.

38.02 Point for the 1/4 sec. cor. of secs. 15 and 22, at propor-  
tionate distance; there is no remaining evidence of the  
original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins.  
in the ground, with brass cap mkd.

1/4  $\frac{S\ 15}{S\ 22}$   
T 28 S R 7 W  
1975

from which

A fir, 15 ins. diam., bears N. 33 3/4° E., 59 lks.  
dist., mkd. 1/4 S15 BT.

A cedar, 16 ins. diam., bears S. 27 3/4° W., 96 lks.  
dist., mkd. 1/4 S22 BT.

From this point, a local corner established by G. R.  
Lecklider, Registered Logging Engineer, No. 4079, in  
1959, bears N. 19° 00' E., 0.092 chs. dist., monumented  
with a rebar, 1/2 in. dia., firmly set, projecting 6 ins.  
above ground, from which bearing trees mkd. by Lecklider:

A fir, 15 ins. diam., bears N. 6 1/2° W., 22 lks.  
dist., with healed blaze.

A fir, 15 ins. diam., bears S. 79 1/2° W., 42 1/2 lks.  
dist., with healed blaze.

Ascend 15 ft. over SE. slope.

38.50 Spur, slopes S. 35° E.; desc. 5 ft. over SW. slope.

38.85 Ravine, drains S. 45° E.; asc. 705 ft. over broken E.  
slope.

61.20 Ridge, bears N. 20° W., and S. 20° E.; desc. 240 ft. over  
broken W. slope.

69.40 Ravine, drains S. 30° W.; asc. 85 ft. over SE. slope.

76.04 The cor. of secs. 15, 16, 21, and 22, perpetuated and re-  
corded by Ben B. Irving, County Surveyor, in 1926, and  
further perpetuated by James W. Byron, Deputy County  
Surveyor, in 1957, monumented with an iron post, 1 1/2 ins.  
diam., firmly set, projecting 10 ins. above ground, with  
brass cap mkd.