

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, **15415**
 T. 28 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

COUNTY SURVEYORS OFFICE

T 28 S
 $\frac{S 16 | S 15}{S 21 | S 22}$
 R 7 W
 1957

from which the remains of the original bearing trees

A root hole, bears S. 29° E., 121 lks. dist., with a down and decayed black oak alongside, 25 ins. diam., no marks visible. (Record, 125 lks.)

A root hole, bears S. 4 1/2° W., 87 lks. dist., with a down and decayed black oak alongside, 17 ins. diam., with scribe marks BT visible in negative on overgrowth. (Record, S. 14° W., 32 lks.)

and the remains of bearing trees mkd. by Irving

A fir snag, 20 ins. diam., bears N. 49 1/4° E., 66 1/2 lks. dist., with healed blaze.

A sawed fir stump, 31 ins. diam., bears S. 34° E., 73 lks. dist., with healed blaze.

A sawed fir stump, 19 ins. diam., bears N. 32 1/2° W., 65 lks. dist., with scribe marks 16 T28S R7W CS BT visible on open blaze.

*Ed. 7/84
G. Sawyer
RM 5-82*

and bearing trees mkd. by Byron

A fir, 16 ins. diam., bears S. 11° E., 59 lks. dist., with healed double blaze.

A fir, 19 ins. diam., bears S. 4° W., 48 lks. dist., with scribe marks T28S R7W visible on partially open double blaze.

A fir, 22 ins. diam., bears N. 12 1/2° W., 14 1/2 lks. dist., mkd. T28S R7W S15 BT. and a new bearing tree

A fir, 12 ins. diam., bears N. 54 1/2° E., 50 lks. dist., mkd. T28S R7W S15 BT.

Ben B. Irving, in 1926, indicated a discrepancy in the original notes and that he used proportionate measurement to determine the corner point from the original bearing trees.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, maple, oak, myrtle, alder, and chinquapin; undergrowth, salal, poson oak, vine maple, rhododendron, Oregon grap, and fern.

N. 0° 59' E., bet. secs. 15 and 16.

Ascend 65 ft. over SW. slope, through scattered timber and dense undergrowth.

4.90

Ridge, bears N. 80° W., and S. 80° E.; desc. 585 ft. over broken NW. slope.