

County Surveyor's Record, Douglas County, Oregon

15416

Dependent Resurvey, Portion of Subdivisional Lines,
T. 28 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

- 30.10 Creek, 1 lk. wide, course N. 75° E.; asc. 50 ft. over SE. slope.
- 33.50 Spur, slopes E.; desc. 100 ft. over NE. slope.
- 36.80 Creek, 1 lk. wide, course N. 60° E.; desc. 80 ft. over broken N. slope.
- 37.10 Point for the 1/4 sec. cor. of secs. 15 and 16, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$
 S 16 | S 15
 T 28 S R 7 W
 1975

from which

A fir, 5 ins. diam., bears S. 70 3/4° E., 85 lks. dist., mkd. 1/4 S15 BT.

A myrtle, 14 ins. diam., bears N. 17 3/4° W., 72 lks. dist., mkd. 1/4 S16 BT.

Descend 20 ft. over N. slope.

- 38.65 Creek, 1 lk. wide, course S. 80° E.; asc. 305 ft. over SE. slope.
- 55.80 Ridge, bears N. 80° E. and S. 80° W.; desc. 85 ft. over N.E. slope.
- 60.45 Ravine, drains N. 85° E.; asc. 140 ft. over SE. slope.
- 65.95 Spur, slopes S. 65° E.; desc. 30 ft. over NE. slope.
- 69.30 Ravine, drains S. 65° E.; asc. 70 ft. over SE. slope.
- 74.20 The cor. of secs. 9, 10, 15, and 16, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1957, monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 28 S
 S 9 | S 10
 S 16 | S 15
 R 7 W
 1957

*FD 7/84
G. BAUCHMAN
RM 3-62*

from which the remains of the original bearing trees

A root hole, bears N. 45° E., 50 lks. dist., with a down black oak alongside, 21 ins. diam., no marks visible.

A madrone, 24 ins. diam., bears S. 13 1/2° E., 17 lks. dist., no marks visible on decayed blaze. (Record, S. 20° E.)

A black oak root crown, 13 ins. diam., bears N. 62° W., 28 lks. dist., with a down black oak alongside, no marks visible. (Record, N. 60° W.)