

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,
T. 28 S., R. 7 W., Willamette Meridian, Oregon

15419

CHAINS

T 28 S R 7 W
S 10
S 15 | C 47
1975

from which

A fir, 15 ins. diam., bears S. 28 1/2° E., 22 lks. dist., mkd. C47 BT.

A fir, 9 ins. diam., bears S. 65° W., 30 1/2 lks. dist., mkd. T28S R7W S15 BT.

A fir, 14 ins. diam., bears N. 76 3/4° W., 7 lks. dist., mkd. T28S R7W S10 BT.

Ascend 50 ft. over SE. slope.

28.10 Spur, slopes S. 25° E.; desc. 2 ft. over SW. slope.

28.25 Ravine, drains S. 25° E.; asc. 150 ft. over SE. slope.

37.07 The cor. of secs. 9, 10, 15, and 16.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, maple, oak, myrtle, cedar, alder, and chinquapin; undergrowth, salal, poison oak, Oregon grape, rhododendron, and fern.

N. 86° 58' W., bet. secs. 9 and 16.

Ascend 55 ft. over SE slope, through heavy timber and dense undergrowth.

2.15 Ridge, bears N. 65° E. and S. 55° W.; desc. 135 ft. over NW. slope.

8.25 Ravine, drains N. 5° E.; asc. 150 ft. over NE. slope.

13.75 Spur, slopes N.; desc. 70 ft. over NW. slope.

17.95 Ravine, drains N. 10° W.; asc. 110 ft. over NE. slope.

23.45 Ridge, bears N. 40° W. and S. 40° E.; desc. 185 ft. over NW. slope.

28.80 Slope changes to SW.

30.95 Spur, slopes S. 40° W.; desc. 195 ft. over SW. slope.

39.35 Point for the 1/4 sec. cor. of secs. 9 and 16, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

1/4 $\frac{S 9}{S 16}$
T 28 S R 7 W
1975

from which

A fir, 17 ins. diam., bears N. 77 1/2° E., 38 lks. dist., mkd. 1/4 S9 BT.