

County Surveyor's Record, Douglas County, Oregon

15420

Dependent Resurvey, Portion of Subdivisional Lines,
T. 28 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

A fir, 6 ins. diam., bears S. 36° E., 51 lks.
dist., mkd. 1/4 S16 BT.

Descend 75 ft. over NW. slope.

42.15 Creek, 1 lk. wide, course S. 50° W.; asc. 135 ft. over SE. slope.

50.70 Spur, slopes S. 10° W.; desc. 100 ft. over SW. slope.

54.65 Ravine, drains S. 10° W.; asc. 110 ft. over SE. slope.

59.30 Spur, slopes S.; desc. 40 ft. over SW. slope.

64.30 Ravine, drains S. 10° E.; asc. 235 ft. over SE. slope.

72.70 Ridge, bears N. 30° E. and S. 30° W.; desc. 110 ft. over NW. slope.

78.70 The cor. of secs. 8, 9, 16, and 17, rehabilitated by Fred Mensch, Cadastral Engineer, in 1924, and not of record, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above ground with brass cap mkd.

T	28	S	R	7	W
	S	8		S	9
	S	17		S	16
	1924				

from which the remains of the original bearing trees

A madrone, 32 ins. diam., bears N. 57 1/4° E., 100 lks. dist., no marks visible on decayed blaze. (Record, N. 65° E., 110 lks.)

A root hole, bears S. 60° W., 8 lks. dist., with a down black oak alongside, 36 ins. diam., no marks visible.

A madrone, 30 ins. diam., bears N. 36 1/4° W., 87 lks. dist., no marks visible on decayed blaze. (Record, N. 35° W.)

and bearing trees mkd. by Mensch

A fir, 11 ins. diam., bears N. 51° E., 32 lks. dist., with scribe marks 7W S Visible on open blaze.

A fir, 25 ins. diam., bears S. 42° E., 24 lks. dist., with healed blaze.

A fir, 26 ins. diam., bears S. 84° W., 42 lks. dist., with healed blaze.

A fir, 28 ins. diam., bears N. 39 3/4° W., 31 lks. dist., with healed blaze.

and a bearing tree of which I have no record

A fir, 20 ins. diam., bears N. 74° E., 37 1/2 lks. dist., with healed blaze.

Add marks 1975 to brass cap.

Land, mountainous.
Soil, rocky clay.