

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines
T. 28 S., R. 7 W., Willamette Meridian, Oregon

15421

CHAINS

Timber, fir, hemlock, cedar, maple, oak, myrtle, alder, and chinquapin; undergrowth, salal, Oregon grape, vine maple, rhododendron, poison oak and fern.

Dependent Resurvey of a Portion of the Boundaries
of Donation Land Claim No. 47,
T. 28 S., R. 7 W., Willamette Meridian, Oregon

(Restoring the survey executed by Josiah A. Burnett,
U. S. Deputy Surveyor, in 1855-56)

From the exterior cor. on the S. bdy. of Donation Land Claim No. 47, perpetuated and recorded by F. C. Frear, Deputy County Surveyor, in 1917, from original evidence no longer in existence, monumented with an iron pipe, 2 ins. diam., firmly set, projecting 4 ins. above ground.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 28 S		
R 7 W		C 47
S 22		_____
1975		

from which

A fir, 10 ins. diam., bears N. 66 1/2° E., 36 1/2 lks. dist., mkd. C47 BT.

A fir, 12 ins. diam., bears N. 50° W., 42 lks. dist., mkd. T28S R7W S22 BT.

Reset iron pipe alongside iron post.

N. 0° 04' E., along the W. bdy. of Claim No. 47.

Descend 35 ft. over NW. slope, through scattering timber and dense undergrowth.

0.80 Intersect line bet. secs. 15 and 22.

The crossing closing cor. of secs. 15 and 22, at intersection with the W. bdy. of Claim No. 47, hereinbefore described.

From this point, the cor. of secs. 14, 15, 22, and 23, bears S. 84° 23' E., 10.02 chs. dist.

Descend 50 ft. over NW. slope.

2.85 Dirt road, 15 lks. wide, bears N. 85° E. and S. 80° W.

3.85 Creek, 1 lk. wide, course N. 80° E.; asc. 125 ft. over SE. slope.

14.85 Spur, slopes N. 70° E.; desc. 50 ft. over NE. slope.

19.60 Ravine, drains E.; asc. 40 ft. over SE. slope.